

## Superprimer

Bonding undercoat for multiple base surfaces



Technical Data Sheet N°933



**USAGE**

**INTERIOR**  
For vertical and horizontal surfaces. For use in all indoor rooms.

**Base surfaces:** For application to all customary structural surfaces, particularly glass, earthenware, non-ferrous metals, normal structural plastics, frame structures, factory pre-lacquered cladding, concrete floors, tiling.

**KEY QUALITIES**

This product permits the decoration of base materials which are considered to be problematic. Suitable for covering with both aqueous and solvent-based finishes.

**DEPLOYMENT**

**PREPARATION OF BASE SURFACES**  
Base surfaces must be entirely free of dust, sound, dry, of uniform quality and thoroughly cleaned. Clean using appropriate mechanical or chemical methods.

**EQUIPMENT FOR APPLICATION**  
For application using a brush or microstar 3/8" (10 mm) roller, and airless sprayer or conventional spray gun.

TYPES OF BASE SURFACES	PREPARATION
Gloss or satin surfaces	Sand down gloss finish and remove dust.
Non-ferrous base materials	Degrease and remove any traces of oxidation.
Plastic and factory pre-lacquered base materials, glass and earthenware	Degrease using an appropriate solvent, sand down gloss finish and remove dust.

**APPLICATION**

Apply a coat of our Superprimer, diluted with 5% of water. In order to achieve the best results, the first top coat should be applied on the following day. Under these conditions, optimum inter-coat adhesion will be achieved. Please note that final hardening may be delayed in cold and humid weather. It is preferable to check the correct bonding of the Superprimer to the base surface, before applying the top coat.

Lightly run a finger nail over a small area – the Superprimer should feel hard under the nail, and must be properly bonded to the base surface.

GENERAL  
CHARACTERISTICS

<b>Appearance</b>	Silk
<b>Coverage</b>	450 sq.Ft/Gal; 58 sq.Ft /Half liter per coat, depending upon the porosity of the base surface
<b>Drying</b>	1 hour (touch dry)
<b>Ready for recoating</b>	Following day (24 hours)
<b>Dry extract</b>	37% (+/-2%) by weight, 33% (+/-2%) by volume
<b>Cleaning of tools</b>	With hot soapy water
<b>Density</b>	1.08 (+/-0.05)
<b>Packaging</b>	0.5 Liter, 1 Gallon
<b>Storage</b>	1 year in unopened original packaging. Protect from frost

PRECAUTIONS

For application between 46°F (8°C) and 95°F (35 °C). Do not apply where the relative humidity exceeds 70%. **Superprimer must not be coloured.**

REGULATORY  
CHARACTERISTICS

<b>VOC (1)</b>	This product contains 0g/l VOC in use.
<b>SAFETY</b>	See the Safety Data Sheet, Compliant with legislation in force.

(1) Volatile Organic Compounds: Directive 2004/42/EC

\* Information on the level of emissions of volatile substances in an interior atmosphere, associated with the risk of toxicity by inhalation, on a scale of class ratings from A+ (very low emissions) to C (high emissions).

Superprimer

**Technical Data Sheet N° 933, 7th May 2018 edition.** This technical data sheet supersedes and replaces previous editions pertaining to the same product. In the light of continuous technical development, it is the responsibility of clients to confirm, prior to application and by consultation with our services, that the present technical data sheet has not been modified by a more recent edition  
**Document available for consultation on our website at [www.ressource-peintures.com](http://www.ressource-peintures.com)**

RESSOURCE