

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010
Issue date: 12/09/2017 Revision date: 22/10/2020 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form : Mixture
Trade name : EXTERIEUR BOIS HES MAT VELOUTE
Product code : 102TP
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Main use category : Professional use
Industrial/Professional use spec : For professional use only
Use of the substance/mixture : Apply paint on interior woodwork / outdoor

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Ressource
Rue de Mousselière
30133 Les Angles - FRANCE
T +33(0)490254245
contact@ressource-decoration.com - www.ressource-peintures.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre, Wolfson Unit	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0344 892 0111	

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Flammable liquids, Category 3 H226
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Extremely flammable liquid and vapour.

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS02

Signal word (CLP) : Warning
Hazard statements (CLP) : H226 - Flammable liquid and vapour.
Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.

EXTERIEUR BOIS HES MAT VELOUTE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

EUH-statements : EUH208 - Contains 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime.
May produce an allergic reaction.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbures, C9 - C11 isoalcanes, cycliques, < 2 % d'aromatiques	(CAS-No.) 64742-48-9 (EC-No.) 919-857-5 (REACH-no) 01-2119463258-33	0 – 4,02675	Flam. Liq. 3, H226 Acute Tox. 3 (Inhalation:vapour), H331 STOT SE 3, H336 Asp. Tox. 1, H304
Isotridecylalcohol, ethoxylated, phosphated, compd. with N,N-dimethylcyclohexanamine	(CAS-No.) 164383-18-0	0 – 1,63	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 2, H411
2-ethylhexanoic acid, zirconium salt	(CAS-No.) 22464-99-9 (EC-No.) 245-018-1 (REACH-no) 01-2119979088-21	≤ 0,45435	Repr. 2, H361
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime	(CAS-No.) 96-29-7 (EC-No.) 202-496-6 (EC Index-No.) 616-014-00-0 (REACH-no) 01-2119539477-28	0 – 0,282	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351
trimethylolpropane	(CAS-No.) 77-99-6 (EC-No.) 201-074-9	0,01 – 0,19122	Repr. 2, H361fd
dipropylene glycol methyl ether substance with a Community workplace exposure limit	(CAS-No.) 34590-94-8 (EC-No.) 252-104-2	≤ 0,12187	Not classified

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : In all cases of doubt, or when symptoms persist, seek medical attention.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact : Continue to rinse eye with clean water for 20-30 minutes, retracting eyelids often. Rinse eyes with water as a precaution.
First-aid measures after ingestion : IF SWALLOWED : Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor. Specific treatment. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : Cracking of the skin. Slight irritation.
Symptoms/effects after eye contact : Eye irritation.
Symptoms/effects after ingestion : Ingestion may cause nausea and vomiting.

EXTERIEUR BOIS HES MAT VELOUTE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable liquid and vapour.
Hazardous decomposition products in case of fire : Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide.

5.3. Advice for firefighters

Precautionary measures fire : Eliminate all ignition sources if safe to do so.
Firefighting instructions : Cool adjacent tanks / containers / drums with water jet. Do not enter fire area without proper protective equipment, including respiratory protection. Prevent fire fighting water from entering the environment. Fight fire from a safe distance or use hoses with support or cannon engine.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information : On exposure to high temperature, may decompose, releasing toxic gases.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Clean up any spills as soon as possible, using an absorbent material to collect it. Avoid contact with skin and eyes.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Liquid spill: take up in dry sand/earth/vermiculite. Cover spill with non combustible material, e.g.: sand, earth, vermiculite.

6.3. Methods and material for containment and cleaning up

For containment : Stop leak without risks if possible. Consult an expert on waste disposal or treatment.
Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Do not allow contact with water. Always wash hands after handling the product. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

EXTERIEUR BOIS HES MAT VELOUTE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Precautions for safe handling	: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Ground/bond container and receiving equipment.
Storage conditions	: Store in a well-ventilated place. Keep cool. Keep container tightly closed.
Heat and ignition sources	: Keep away from open flames, hot surfaces and sources of ignition.
Information on mixed storage	: Keep out of reach of children.
Storage area	: Store in a well-ventilated place. Store away from heat.
Special rules on packaging	: Keep only in original container. Store in a closed container.
Packaging materials	: Keep only in the original container in a cool, well-ventilated place away from combustible materials.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

dipropylene glycol methyl ether (34590-94-8)	
EU - Occupational Exposure Limits	
Local name	(2-Methoxymethylethoxy)-propanol
IOELV TWA (mg/m ³)	308 mg/m ³
IOELV TWA (ppm)	50 ppm
Notes	Skin
Austria - Occupational Exposure Limits	
Local name	Dipropylenglykolmonomethylether (Isomerengemisch)
MAK Daily average value (mg/m ³)	307 mg/m ³
MAK Daily average value (ppm)	50 ppm
MAK Short time value [mg/m ³]	614 mg/m ³
MAK Short time value [ppm]	100 ppm
Remark (AT)	H
Belgium - Occupational Exposure Limits	
Local name	Dipropylèneglycolmonométhyléther
Limit value [mg/m ³]	308 mg/m ³
Limit value [ppm]	50 ppm
Remark (BE)	D
Bulgaria - Occupational Exposure Limits	
Local name	пропанол•
OEL TWA (mg/m ³)	308 mg/m ³
Croatia - Occupational Exposure Limits	
Local name	(2-Metoksimetiletoksi)– – propanol
GVI (granična vrijednost izloženosti) (mg/m ³)	308 mg/m ³

EXTERIEUR BOIS HES MAT VELOUTE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

dipropylene glycol methyl ether (34590-94-8)	
GVI (granična vrijednost izloženosti) (ppm)	50 ppm
Naznake (HR)	K, EU*
Czech Republic - Occupational Exposure Limits	
Local name	propanol(2-Methoxymethylethoxy)-(technická sm s isomer)
Expoziční limity (PEL) (mg/m ³)	270 mg/m ³
Expoziční limity (PEL) (ppm)	44,6 ppm
Expoziční limity (NPK-P) (mg/m ³)	550 mg/m ³
Expoziční limity (NPK-P) (ppm)	90,8 ppm
Remark (CZ)	D
Denmark - Occupational Exposure Limits	
Local name	Dipropylenglycolmethylether (1994)
Grænseværdi (8 timer) (mg/m ³)	300 mg/m ³
Grænseværdi (8 timer) (ppm)	50 ppm
Anmærkninger (DK)	EH
Estonia - Occupational Exposure Limits	
Local name	Dipropüleenglükooli monometüüleeter (2-etoksümetüületoksi)-propanool
OEL TWA (mg/m ³)	308 mg/m ³
OEL TWA (ppm)	50 ppm
Finland - Occupational Exposure Limits	
Local name	(2-Metoksimetyylietoksi)- propanoli
HTP-arvo (8h) (mg/m ³)	310 mg/m ³
HTP-arvo (8h) (ppm)	50 ppm
France - Occupational Exposure Limits	
Local name	(2-méthoxyméthylethoxy)-propanol
VME [mg/m ³]	308 mg/m ³
VME [ppm]	50 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
TRGS 900 Local name	(2-Methoxymethylethoxy)propanol(Isomerengemisch)
Occupational exposure limit value (mg/m ³)	310 mg/m ³
Occupational exposure limit value (ppm)	50 ppm
TRGS 900 Remark	DFG,EU
Greece - Occupational Exposure Limits	
OEL TWA (mg/m ³)	600 mg/m ³
OEL TWA (ppm)	100 ppm
OEL STEL (mg/m ³)	900 mg/m ³
OEL STEL (ppm)	150 ppm
Hungary - Occupational Exposure Limits	
Local name	(2-METOXIMETILETOXI)-PROPANOL (Dipropilénglikol-monometil-éter)
AK-érték	308 mg/m ³
CK-érték	308 mg/m ³

EXTERIEUR BOIS HES MAT VELOUTE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

dipropylene glycol methyl ether (34590-94-8)	
Megjegyzések (HU)	EU1
Ireland - Occupational Exposure Limits	
Local name	(2-Methoxymethylethoxy)-I-propanol
OEL (8 hours ref) (mg/m ³)	308 mg/m ³
OEL (8 hours ref) (ppm)	50 ppm
Notes (IE)	Sk, IOELV
Italy - Occupational Exposure Limits	
Local name	(2-Metossimetilotossi)-propanolo
OEL TWA (mg/m ³)	308 mg/m ³
OEL TWA (ppm)	50 ppm
Latvia - Occupational Exposure Limits	
Local name	Metoksi propoksi propanols (dipropilēnglikola monometilēteris,DPM)
OEL TWA (mg/m ³)	308 mg/m ³
OEL TWA (ppm)	50 ppm
Lithuania - Occupational Exposure Limits	
Local name	2-(2-metoksi propoksi)-propanolis (2-etoksimetiletoksi)-propanolis, dipropilenglikolio monometileteris
IPRV (mg/m ³)	300 mg/m ³
IPRV (ppm)	50 ppm
TPRV (mg/m ³)	450 mg/m ³
TPRV (ppm)	75 ppm
Remark (LT)	O
Malta - Occupational Exposure Limits	
Local name	(2-Methoxymethylethoxy)-propanol
OEL TWA (mg/m ³)	308 mg/m ³
OEL TWA (ppm)	50 ppm
Netherlands - Occupational Exposure Limits	
Local name	Dipropyleenglycolmethylether
Grenswaarde TGG 8H (mg/m ³)	300 mg/m ³
Poland - Occupational Exposure Limits	
Local name	(2-Metoksymetyloetoksy)propanol
NDS (mg/m ³)	240 mg/m ³
NDSCh (mg/m ³)	480 mg/m ³
Portugal - Occupational Exposure Limits	
Local name	2-Metoximetiletoksiopropanol (DPGME)
OEL TWA (ppm)	100 ppm
OEL STEL (ppm)	150 ppm
Romania - Occupational Exposure Limits	
Local name	(2-metoximetiletoksi)-propanol
OEL TWA (mg/m ³)	308 mg/m ³
OEL TWA (ppm)	50 ppm

EXTERIEUR BOIS HES MAT VELOUTE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

dipropylene glycol methyl ether (34590-94-8)	
Slovenia - Occupational Exposure Limits	
Local name	(2-metoksimetiletoksi)propanol (mešanica izomer)
OEL TWA (mg/m ³)	308 mg/m ³
OEL TWA (ppm)	50 ppm
Spain - Occupational Exposure Limits	
Local name	Éter metílico de dipropilenglicol
VLA-ED (mg/m ³)	308 mg/m ³
VLA-ED (ppm)	50 ppm
Notes	Vía dérmica: (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante. Para más información véase el Apartado 5 de este documento.), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país.)
Sweden - Occupational Exposure Limits	
Local name	Dipropylene glycol monomethyl ether
nivågränsvärde (NVG) (mg/m ³)	300 mg/m ³
nivågränsvärde (NVG) (ppm)	50 ppm
kortidsvärde (KTV) (mg/m ³)	450 mg/m ³
kortidsvärde (KTV) (ppm)	75 ppm
United Kingdom - Occupational Exposure Limits	
Local name	(2-methoxymethylethoxy) propanol
WEL TWA (mg/m ³)	308 mg/m ³
WEL TWA (ppm)	50 ppm
Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Norway - Occupational Exposure Limits	
Local name	(2-Metoksymetyletoksy)-propanol
Grenseverdier (AN) (mg/m ³)	300 mg/m ³
Grenseverdier (AN) (ppm)	50 ppm
Merknader (NO)	H
Switzerland - Occupational Exposure Limits	
Local name	Oxyde de dipropylèneglycolméthyle (mélange d'isomères)
MAK (mg/m ³)	300 mg/m ³
MAK (ppm)	50 ppm
KZGW (mg/m ³)	300 mg/m ³
KZGW (ppm)	50 ppm
Remark	15 min

EXTERIEUR BOIS HES MAT VELOUTE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Protective clothing. Wear gas mask if conc. in air >. Safety glasses. Gloves.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):**Environmental exposure controls:**

Avoid release to the environment.

Consumer exposure controls:

Avoid contact during pregnancy/while nursing. The substance is not classified for human health hazards or for environment effects and it is not PBT or vPvB so that no exposure assessment or risk characterisation is required. For tasks where the intervention of workers is required, the substance must be handled in accordance with good industrial hygiene and safety procedures.

Other information:

Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: white.
Odour	: No data available
Odour threshold	: No data available
pH	: > 7
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: ≥ 61 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Density	: 1,44 g/cm ³
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available

EXTERIEUR BOIS HES MAT VELOUTE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Viscosity, kinematic	: No data available
Viscosity, dynamic	: 500 – 2000 cP
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : < 300 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, nitrogen oxides (NOx).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

Hydrocarbures, C9 - C11 isoalcanes, cycliques, < 2 % d'aromatiques (64742-48-9)

LD50 oral rat	> 5000 mg/kg (OECD 401)
LD50 dermal rabbit	≥ 3160 mg/kg
LC50 Inhalation - Rat	> 4951 mg/m ³

2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (96-29-7)

LD50 oral rat	900 mg/kg
LD50 dermal rat	1000 mg/kg
LC50 Inhalation - Rat	13,2 mg/l

Isotridecylalcohol, ethoxylated, phosphated, compd. with N,N-dimethylcyclohexanamine (164383-18-0)

LD50 oral rat	> 2500 mg/kg
---------------	--------------

EXTERIEUR BOIS HES MAT VELOUTE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

2-ethylhexanoic acid, zirconium salt (22464-99-9)

LD50 oral rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Skin corrosion/irritation	: Not classified pH: > 7
Serious eye damage/irritation	: Not classified pH: > 7
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Hydrocarbures, C9 - C11 isoalcanes, cycliques, < 2 % d'aromatiques (64742-48-9)

LC50 fish 1	> 1000 mg/l 96 Hours (Oncorhynchus mykiss)
LC50 fish 2	2200 mg/l 96 Hours (Pimephales promelas)
EC50 Daphnia 1	100 mg/l 48 Hours (Chaetogammarus marinus)
ErC50 (algae)	> 1000 mg/l 72 Hours (Pseudokirchneriella subcapitata)
NOEC (acute)	100 mg/l 72 Hours (Pseudokirchneriella subcapitata)
NOEC (chronic)	0,13 mg/l (Oncorhynchus mykiss)

2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (96-29-7)

LC50 fish 1	> 100 mg/l 96 Hours (Oryzias latipes)
EC50 Daphnia 1	201 mg/l 48 Hours (Daphnia magna)
ErC50 (algae)	11,8 mg/l 72 Hours

Isotridecylalcohol, ethoxylated, phosphated, compd. with N,N-dimethylcyclohexanamine (164383-18-0)

LC50 fish 1	1 – 10 mg/l
-------------	-------------

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

EXTERIEUR BOIS HES MAT VELOUTE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available



SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Avoid release to the environment. Discharging into rivers and drains is forbidden. Dispose in a safe manner in accordance with local/national regulations.
Additional information	: Flammable vapours may accumulate in the container.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 01 12 - waste paint and varnish other than those mentioned in 08 01 11

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

ADR	IMDG	IATA	ADN	RID
14.1. UN number				
UN 1263	UN 1263	UN 1263	Not regulated	Not regulated
14.2. UN proper shipping name				
PAINT (MIXTURE ;)	PAINT (MIXTURE ;)	(MIXTURE ;)	Not regulated	Not regulated
Transport document description				
UN 1263 PAINT (MIXTURE ;), 3, III, (D/E)	UN 1263 PAINT (MIXTURE ;), 3, III	UN 1263 (MIXTURE ;)	Not regulated	Not regulated
14.3. Transport hazard class(es)				
3	3	Not applicable	Not regulated	Not regulated
		Not applicable	Not regulated	Not regulated
14.4. Packing group				
III	III	Not applicable	Not regulated	Not regulated
14.5. Environmental hazards				
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No	Not regulated	Not regulated
No supplementary information available				
14.6. Special precautions for user				

Overland transport


Transport regulations (ADR) : Not subject to this regulation if Q <450l

EXTERIEUR BOIS HES MAT VELOUTE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Classification code (ADR) : F1
Special provisions (ADR) : 163, 640E, 650, 367
Limited quantities (ADR) : 5I
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T2
Portable tank and bulk container special provisions (ADR) : TP1, TP29
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 30
Orange plates :



Tunnel restriction code (ADR) : D/E
EAC code : •3YE

Transport by sea

Transport regulations (IMDG) : Non soumis à la réglementation IMDG si Q < 30 l
Special provisions (IMDG) : 163, 223, 955, 367
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T2
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : A
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

Air transport

No data available

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

Reference code	Applicable on
3(a)	EXTERIEUR BOIS HES MAT VELOUTE
3(b)	2-ethylhexanoic acid, zirconium salt ; 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

EXTERIEUR BOIS HES MAT VELOUTE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : < 300 g/l

15.1.2. National regulations

France

Occupational diseases : RG 25 - Affections consécutives à l'inhalation de poussières minérales renfermant de la silice cristalline (quartz, cristobalite, tridymite), des silicates cristallins (kaolin, talc), du graphite ou de la houille.
RG 36 - Affections provoquées par les huiles et graisses d'origine minérale ou de synthèse
RG 84 - Affections engendrées par les solvants organiques liquides à usage professionnel

Other information, restrictions and prohibition regulations : VOC Directive 2004/42/EC - Decorative paints and varnishes
Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Germany

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
LC50	Median lethal concentration
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
SDS	Safety Data Sheet
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LD50	Median lethal dose
PBT	Persistent Bioaccumulative Toxic
vPvB	Very Persistent and Very Bioaccumulative
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

EXTERIEUR BOIS HES MAT VELOUTE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Data sources	: Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
Training advice	: Normal use of this product shall imply use in accordance with the instructions on the packaging.
Other information	: The working conditions of the user are not known to us, the information provided in this safety data sheet are based on the State of our knowledge and on both national and Community regulations. The mixture should not be used for other uses as those specified in section 1 without first obtaining prior written handling instructions. It is always the responsibility of the user to take all the necessary measures to meet the requirements of the laws and local regulations. The information provided in this safety data sheet should be considered a description of the safety requirements to this mixture and not as a guarantee of the properties of it.

The working conditions of the user are not known to us, the information provided in this safety data sheet are based on the State of our knowledge and on both national and Community regulations. The mixture should not be used for other uses as those specified in section 1 without first obtaining prior written handling instructions. It is always the responsibility of the user to take all the necessary measures to meet the requirements of the laws and local regulations. The information provided in this safety data sheet should be considered a description of the safety requirements to this mixture and not as a guarantee of the properties of it.

Full text of H- and EUH-statements:	
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H332	Harmful if inhaled.

EXTERIEUR BOIS HES MAT VELOUTE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
H411	Toxic to aquatic life with long lasting effects.
EUH208	Contains 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime. May produce an allergic reaction.

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.