

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830
Issue date: 31/08/2017 Revision date: 22/10/2020 Version: 3.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : IMPRESSION SOLVANTEE
Product code : 360ST
Type of product : PAINT
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Ressource
Rue de Mousselière
30133 Les Angles - FRANCE
T +33(0)490254245
contact@ressource-decoration.com - www.ressource-peintures.com

1.4. Emergency telephone number

| Country | Organisation/Company | Address | Emergency number | Comment |
|----------------|---|---|------------------|---------|
| United Kingdom | National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre, Wolfson Unit | Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle | 0344 892 0111 | |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

Signal word (CLP) : Warning
Hazard statements (CLP) : H226 - Flammable liquid and vapour.
Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.

IMPRESSION SOLVANTEE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

EUH-statements : EUH208 - Contains 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime.
May produce an allergic reaction.

2.3. Other hazards

Other hazards not contributing to the classification : The product does not meet the PBT and vPvB classification criteria.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|---|---|---------------------|---|
| Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics | (CAS-No.) 64742-48-9 (EC-No.) 919-857-5 (REACH-no) 01-2119463258-33 | 2,1545 – 4,309 | Flam. Liq. 3, H226 Acute Tox. 3 (Inhalation:vapour), H331 STOT SE 3, H336 Asp. Tox. 1, H304 |
| Hydrocarbures, C9 - C11 isoalcanes, cycliques, < 2 % d'aromatiques | (CAS-No.) 64742-48-9 (EC-No.) 919-857-5 (REACH-no) 01-2119463258-33 | 1,88075 – 3,7615 | Flam. Liq. 3, H226 Acute Tox. 3 (Inhalation:vapour), H331 STOT SE 3, H336 Asp. Tox. 1, H304 |
| 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime | (CAS-No.) 96-29-7 (EC-No.) 202-496-6 (EC Index-No.) 616-014-00-0 (REACH-no) 01-2119539477-28 | 0,1 – 1 | Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:vapour), H332 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351 |
| dipropylene glycol methyl ether substance with a Community workplace exposure limit | (CAS-No.) 34590-94-8 (EC-No.) 252-104-2 | ≤ 0,07259 | Not classified |

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : In all cases of doubt, or when symptoms persist, seek medical attention.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact : Wash with plenty of water (during 20 minutes minimum) with eyes wide open after taking off soft contact lenses and immediately take medical advice. Rinse eyes with water as a precaution.
First-aid measures after ingestion : IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

IMPRESSION SOLVANTEE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.
Hazardous decomposition products in case of fire : On burning: release of carbon monoxide - carbon dioxide.

5.3. Advice for firefighters

Firefighting instructions : Cool adjacent tanks / containers / drums with water jet.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Do not allow surface water to enter drains and sewers as this will create a potential explosive hazard. If this occurs inform local authorities immediately.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Store in a well-ventilated place. Keep cool. Keep container tightly closed.
Incompatible products : Strong acids. Oxidizing agent. Strong bases.
Heat and ignition sources : Keep away from open flames, hot surfaces and sources of ignition.
Storage area : Store in a well-ventilated place.

IMPRESSION SOLVANTEE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Special rules on packaging : Keep only in original container. Store in a closed container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| dipropylene glycol methyl ether (34590-94-8) | |
|--|--|
| EU - Occupational Exposure Limits | |
| Local name | (2-Methoxymethylethoxy)-propanol |
| IOELV TWA (mg/m ³) | 308 mg/m ³ |
| IOELV TWA (ppm) | 50 ppm |
| Notes | Skin |
| Austria - Occupational Exposure Limits | |
| Local name | Dipropylenglykolmonomethylether (Isomerengemisch) |
| MAK Daily average value (mg/m ³) | 307 mg/m ³ |
| MAK Daily average value (ppm) | 50 ppm |
| MAK Short time value [mg/m ³] | 614 mg/m ³ |
| MAK Short time value [ppm] | 100 ppm |
| Remark (AT) | H |
| Belgium - Occupational Exposure Limits | |
| Local name | Dipropylèneglycolmonométhyléther |
| Limit value [mg/m ³] | 308 mg/m ³ |
| Limit value [ppm] | 50 ppm |
| Remark (BE) | D |
| Bulgaria - Occupational Exposure Limits | |
| Local name | пропанол* |
| OEL TWA (mg/m ³) | 308 mg/m ³ |
| Croatia - Occupational Exposure Limits | |
| Local name | (2-Metoksimetiletoksi)– – propanol |
| GVI (granična vrijednost izloženosti) (mg/m ³) | 308 mg/m ³ |
| GVI (granična vrijednost izloženosti) (ppm) | 50 ppm |
| Naznake (HR) | K, EU* |
| Czech Republic - Occupational Exposure Limits | |
| Local name | propanol(2-Methoxymethylethoxy)-(technická sm s isomer) |
| Expoziční limity (PEL) (mg/m ³) | 270 mg/m ³ |
| Expoziční limity (PEL) (ppm) | 44,6 ppm |
| Expoziční limity (NPK-P) (mg/m ³) | 550 mg/m ³ |
| Expoziční limity (NPK-P) (ppm) | 90,8 ppm |
| Remark (CZ) | D |
| Denmark - Occupational Exposure Limits | |
| Local name | Dipropylenglycolmethylether (1994) |

IMPRESSION SOLVANTEE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| dipropylene glycol methyl ether (34590-94-8) | |
|--|--|
| Grænseværdi (8 timer) (mg/m ³) | 300 mg/m ³ |
| Grænseværdi (8 timer) (ppm) | 50 ppm |
| Anmærkninger (DK) | EH |
| Estonia - Occupational Exposure Limits | |
| Local name | Dipropüleenglükooli monometüüleeter (2-etoksümetüületoksü)-propanool |
| OEL TWA (mg/m ³) | 308 mg/m ³ |
| OEL TWA (ppm) | 50 ppm |
| Finland - Occupational Exposure Limits | |
| Local name | (2-Metoksimetyylietoksi)- propanoli |
| HTP-arvo (8h) (mg/m ³) | 310 mg/m ³ |
| HTP-arvo (8h) (ppm) | 50 ppm |
| France - Occupational Exposure Limits | |
| Local name | (2-méthoxyméthylethoxy)-propanol |
| VME [mg/m ³] | 308 mg/m ³ |
| VME [ppm] | 50 ppm |
| Germany - Occupational Exposure Limits (TRGS 900) | |
| TRGS 900 Local name | (2-Methoxymethylethoxy)propanol(Isomerengemisch) |
| Occupational exposure limit value (mg/m ³) | 310 mg/m ³ |
| Occupational exposure limit value (ppm) | 50 ppm |
| TRGS 900 Remark | DFG,EU |
| Greece - Occupational Exposure Limits | |
| OEL TWA (mg/m ³) | 600 mg/m ³ |
| OEL TWA (ppm) | 100 ppm |
| OEL STEL (mg/m ³) | 900 mg/m ³ |
| OEL STEL (ppm) | 150 ppm |
| Hungary - Occupational Exposure Limits | |
| Local name | (2-METOXIMETILETOXI)-PROPANOL (Dipropilénlikol-monometil-éter) |
| AK-érték | 308 mg/m ³ |
| CK-érték | 308 mg/m ³ |
| Megjegyzések (HU) | EU1 |
| Ireland - Occupational Exposure Limits | |
| Local name | (2-Methoxymethylethoxy)-I-propanol |
| OEL (8 hours ref) (mg/m ³) | 308 mg/m ³ |
| OEL (8 hours ref) (ppm) | 50 ppm |
| Notes (IE) | Sk, IOELV |
| Italy - Occupational Exposure Limits | |
| Local name | (2-Metossimetilotossi)-propanolo |
| OEL TWA (mg/m ³) | 308 mg/m ³ |
| OEL TWA (ppm) | 50 ppm |

IMPRESSION SOLVANTEE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| dipropylene glycol methyl ether (34590-94-8) | |
|---|---|
| Latvia - Occupational Exposure Limits | |
| Local name | Metoksipropoksi propanols (dipropilēnglikola monometilēteris,DPM) |
| OEL TWA (mg/m ³) | 308 mg/m ³ |
| OEL TWA (ppm) | 50 ppm |
| Lithuania - Occupational Exposure Limits | |
| Local name | 2-(2-metoksipropoksi)-propanolis (2-etoksimetiletoksi)-propanolis, dipropilenglikolio monometileteris |
| IPRV (mg/m ³) | 300 mg/m ³ |
| IPRV (ppm) | 50 ppm |
| TPRV (mg/m ³) | 450 mg/m ³ |
| TPRV (ppm) | 75 ppm |
| Remark (LT) | O |
| Malta - Occupational Exposure Limits | |
| Local name | (2-Methoxymethylethoxy)-propanol |
| OEL TWA (mg/m ³) | 308 mg/m ³ |
| OEL TWA (ppm) | 50 ppm |
| Netherlands - Occupational Exposure Limits | |
| Local name | Dipropyleenglycolmethylether |
| Grenswaarde TGG 8H (mg/m ³) | 300 mg/m ³ |
| Poland - Occupational Exposure Limits | |
| Local name | (2-Metoksymetyloetoksy)propanol |
| NDS (mg/m ³) | 240 mg/m ³ |
| NDSch (mg/m ³) | 480 mg/m ³ |
| Portugal - Occupational Exposure Limits | |
| Local name | 2-Metoximetiletoksiopropanol (DPGME) |
| OEL TWA (ppm) | 100 ppm |
| OEL STEL (ppm) | 150 ppm |
| Romania - Occupational Exposure Limits | |
| Local name | (2-metoximetiletoksi)-propanol |
| OEL TWA (mg/m ³) | 308 mg/m ³ |
| OEL TWA (ppm) | 50 ppm |
| Slovenia - Occupational Exposure Limits | |
| Local name | (2-metoksimetiletoksi)propanol (mešanica izomer) |
| OEL TWA (mg/m ³) | 308 mg/m ³ |
| OEL TWA (ppm) | 50 ppm |
| Spain - Occupational Exposure Limits | |
| Local name | Éter metílico de dipropilenglicol |
| VLA-ED (mg/m ³) | 308 mg/m ³ |
| VLA-ED (ppm) | 50 ppm |

IMPRESSION SOLVANTEE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

dipropylene glycol methyl ether (34590-94-8)

| | |
|-------|---|
| Notes | Vía dérmica: (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante. Para más información véase el Apartado 5 de este documento.), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país.) |
|-------|---|

Sweden - Occupational Exposure Limits

| | |
|---|-------------------------------------|
| Local name | Dipropylene glycol monomethyl ether |
| nivågränsvärde (NVG) (mg/m ³) | 300 mg/m ³ |
| nivågränsvärde (NVG) (ppm) | 50 ppm |
| kortidsvärde (KTV) (mg/m ³) | 450 mg/m ³ |
| kortidsvärde (KTV) (ppm) | 75 ppm |

United Kingdom - Occupational Exposure Limits

| | |
|------------------------------|---|
| Local name | (2-methoxymethylethoxy) propanol |
| WEL TWA (mg/m ³) | 308 mg/m ³ |
| WEL TWA (ppm) | 50 ppm |
| Remark (WEL) | Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity) |

Norway - Occupational Exposure Limits

| | |
|---|---------------------------------|
| Local name | (2-Metoksymetyletoksy)-propanol |
| Grenseverdier (AN) (mg/m ³) | 300 mg/m ³ |
| Grenseverdier (AN) (ppm) | 50 ppm |
| Merknader (NO) | H |

Switzerland - Occupational Exposure Limits

| | |
|---------------------------|--|
| Local name | Oxyde de dipropylèneglycolméthyle (mélange d'isomères) |
| MAK (mg/m ³) | 300 mg/m ³ |
| MAK (ppm) | 50 ppm |
| KZGW (mg/m ³) | 300 mg/m ³ |
| KZGW (ppm) | 50 ppm |
| Remark | 15 min |

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Protective clothing. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Eye protection. Gloves.

Hand protection:

Protective gloves

IMPRESSION SOLVANTEE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---------------------------|
| Physical state | : Liquid |
| Colour | : white. |
| Odour | : Organic solvents. |
| Odour threshold | : No data available |
| pH | : > 7 |
| Relative evaporation rate (butylacetate=1) | : No data available |
| Melting point | : Not applicable |
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : 48 °C |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Flammability (solid, gas) | : Not applicable |
| Vapour pressure | : No data available |
| Relative vapour density at 20 °C | : No data available |
| Relative density | : 1,685 |
| Density | : 1,685 g/cm ³ |
| Solubility | : No data available |
| Partition coefficient n-octanol/water (Log Pow) | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : 500 – 2000 cP |
| Explosive properties | : No data available |
| Oxidising properties | : No data available |
| Explosive limits | : No data available |

9.2. Other information

VOC content : < 300 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

IMPRESSION SOLVANTEE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, nitrogen oxides (NO_x), NH₃, sulphur compounds.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Hydrocarbures, C9 - C11 isoalcanes, cycliques, < 2 % d'aromatiques (64742-48-9)

| | |
|-----------------------|--------------------------|
| LD50 oral rat | > 5000 mg/kg (OECD 401) |
| LD50 dermal rabbit | ≥ 3160 mg/kg |
| LC50 Inhalation - Rat | > 4951 mg/m ³ |

2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (96-29-7)

| | |
|-----------------------|------------|
| LD50 oral rat | 900 mg/kg |
| LD50 dermal rat | 1000 mg/kg |
| LC50 Inhalation - Rat | 13,2 mg/l |

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)

| | |
|---------------------------------|--------------|
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rabbit | > 5000 mg/kg |
| LC50 Inhalation - Rat (Vapours) | > 5 mg/l/4h |

Skin corrosion/irritation : Not classified
pH: > 7
Serious eye damage/irritation : Not classified
pH: > 7
Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified

IMPRESSION SOLVANTEE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Hazardous to the aquatic environment, short-term (acute) : Not classified

Hazardous to the aquatic environment, long-term (chronic) : Not classified

Hydrocarbures, C9 - C11 isoalcanes, cycliques, < 2 % d'aromatiques (64742-48-9)

| | |
|----------------|--|
| LC50 fish 1 | > 1000 mg/l 96 Hours (Oncorhynchus mykiss) |
| LC50 fish 2 | 2200 mg/l 96 Hours (Pimephales promelas) |
| EC50 Daphnia 1 | 100 mg/l 48 Hours (Chaetogammarus marinus) |
| ErC50 (algae) | > 1000 mg/l 72 Hours (Pseudokirchneriella subcapitata) |
| NOEC (acute) | 100 mg/l 72 Hours (Pseudokirchneriella subcapitata) |
| NOEC (chronic) | 0,13 mg/l (Oncorhynchus mykiss) |

2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (96-29-7)

| | |
|----------------|---------------------------------------|
| LC50 fish 1 | > 100 mg/l 96 Hours (Oryzias latipes) |
| EC50 Daphnia 1 | 201 mg/l 48 Hours (Daphnia magma) |
| ErC50 (algae) | 11,8 mg/l 72 Hours |

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)

| | |
|---------------|---|
| LC50 fish 1 | > 1000 mg/l 96 heures (Oncorhynchus mykiss) |
| ErC50 (algae) | > 1000 mg/l (Pseudokirchneriella subcapitata) |

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Dispose of this material and its container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

IMPRESSION SOLVANTEE



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

| | |
|--|--|
| Sewage disposal recommendations | : Disposal must be done according to official regulations. |
| Product/Packaging disposal recommendations | : Completely empty the packaging prior to decontamination. Discharging into rivers and drains is forbidden. |
| Additional information | : Flammable vapours may accumulate in the container. |
| Ecology - waste materials | : Ne pas rejeter dans le tout à l'égout. Avoid release to the environment. |
| European List of Waste (LoW) code | : 08 01 11* - waste paint and varnish containing organic solvents or other dangerous substances |
| HP Code | : HP3 - "Flammable:" — flammable liquid waste: liquid waste having a flash point below 60 °C or waste gas oil, diesel and light heating oils having a flash point > 55 °C and ≤ 75 °C; — flammable pyrophoric liquid and solid waste: solid or liquid waste which, even in small quantities, is liable to ignite within five minutes after coming into contact with air; — flammable solid waste: solid waste which is readily combustible or may cause or contribute to fire through friction; — flammable gaseous waste: gaseous waste which is flammable in air at 20 °C and a standard pressure of 101.3 kPa; — water reactive waste: waste which, in contact with water, emits flammable gases in dangerous quantities; — other flammable waste: flammable aerosols, flammable self-heating waste, flammable organic peroxides and flammable self-reactive waste. |
| R code/ D code | : R1 - Use principally as a fuel or other means to generate energy |

SECTION 14: Transport information

In accordance with ADR / IMDG

| ADR | IMDG |
|---|---|
| 14.1. UN number | |
| UN 1263 | UN 1263 |
| 14.2. UN proper shipping name | |
| PAINT | PAINT |
| Transport document description | |
| UN 1263 PAINT, 3, III, (D/E) | UN 1263 PAINT, 3, III |
| 14.3. Transport hazard class(es) | |
| 3 | 3 |
|  |  |
| 14.4. Packing group | |
| III | III |
| 14.5. Environmental hazards | |
| Dangerous for the environment : No | Dangerous for the environment : No Marine pollutant : No |
| No supplementary information available | |

14.6. Special precautions for user


| | |
|-------------------------------|---|
| Special transport precautions | : Avoid release to the environment. |
| Overland transport | |
| Transport regulations (ADR) | : Not subject to this regulation if Q <450l |
| Classification code (ADR) | : F1 |
| Special provisions (ADR) | : 163, 640E, 650, 367 |
| Limited quantities (ADR) | : 5I |

IMPRESSION SOLVANTEE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T2
Portable tank and bulk container special provisions (ADR) : TP1, TP29
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 30
Orange plates :



Tunnel restriction code (ADR) : D/E

Transport by sea

Transport regulations (IMDG) : Non soumis à la réglementation IMDG si Q < 30 l
Special provisions (IMDG) : 163, 223, 955, 367
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T2
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : A
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

| Reference code | Applicable on |
|----------------|---|
| 3(a) | IMPRESSION SOLVANTEE |
| 3(b) | 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime ; Hydrocarbures, C9 - C11 isoalcanes, cycliques, < 2 % d'aromatiques |

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : < 300 g/l

IMPRESSION SOLVANTEE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

15.1.2. National regulations

France

- Occupational diseases : RG 25 - Affections consécutives à l'inhalation de poussières minérales renfermant de la silice cristalline (quartz, cristobalite, tridymite), des silicates cristallins (kaolin, talc), du graphite ou de la houille.
RG 84 - Affections engendrées par les solvants organiques liquides à usage professionnel
- Other information, restrictions and prohibition regulations : Labelling according to Regulation (EC) No. 1272/2008 [CLP]
VOC Directive 2004/42/EC - Decorative paints and varnishes
Labelling of building products or products used for wall or floor coatings and paints and varnishes concerning their emissions of volatile pollutants (Order of 19 April 2011)
Classification according to directives 67/548/EEC and 1999/45/EC

Germany

- Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1)
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

- SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

- Class for fire hazard : Class II-1
Store unit : 5 liter
Classification remarks : R10 <H226>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:

| | |
|-------|---|
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| LC50 | Median lethal concentration |
| CLP | Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 |
| ADN | European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways |
| SDS | Safety Data Sheet |
| IATA | International Air Transport Association |
| IMDG | International Maritime Dangerous Goods |
| LD50 | Median lethal dose |
| PBT | Persistent Bioaccumulative Toxic |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006 |
| vPvB | Very Persistent and Very Bioaccumulative |
| ATE | Acute Toxicity Estimate |

IMPRESSION SOLVANTEE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

- Data sources : Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
- Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.
- Other information : The working conditions of the user are not known to us, the information provided in this safety data sheet are based on the State of our knowledge and on both national and Community regulations. The mixture should not be used for other uses as those specified in section 1 without first obtaining prior written handling instructions. It is always the responsibility of the user to take all the necessary measures to meet the requirements of the laws and local regulations. The information provided in this safety data sheet should be considered a description of the safety requirements to this mixture and not as a guarantee of the properties of it.

The working conditions of the user are not known to us, the information provided in this safety data sheet are based on the State of our knowledge and on both national and Community regulations. The mixture should not be used for other uses as those specified in section 1 without first obtaining prior written handling instructions. It is always the responsibility of the user to take all the necessary measures to meet the requirements of the laws and local regulations. The information provided in this safety data sheet should be considered a description of the safety requirements to this mixture and not as a guarantee of the properties of it.

| Full text of H- and EUH-statements: | |
|-------------------------------------|--|
| Acute Tox. 3 (Inhalation:vapour) | Acute toxicity (inhalation:vapour) Category 3 |
| Acute Tox. 4 (Dermal) | Acute toxicity (dermal), Category 4 |
| Acute Tox. 4 (Inhalation:vapour) | Acute toxicity (inhalation:vapour) Category 4 |
| Acute Tox. 4 (Oral) | Acute toxicity (oral), Category 4 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Carc. 2 | Carcinogenicity, Category 2 |
| Eye Dam. 1 | Serious eye damage/eye irritation, Category 1 |
| Flam. Liq. 3 | Flammable liquids, Category 3 |
| Skin Sens. 1 | Skin sensitisation, Category 1 |
| STOT SE 3 | Specific target organ toxicity — Single exposure, Category 3, Narcosis |
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H312 | Harmful in contact with skin. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H331 | Toxic if inhaled. |
| H332 | Harmful if inhaled. |
| H336 | May cause drowsiness or dizziness. |
| H351 | Suspected of causing cancer. |
| EUH208 | Contains 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime. May produce an allergic reaction. |

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.