

Safety Data Sheetaccording to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878
Issue date: 31/08/2017 Revision date: 28/08/2020 Version: 1.0**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture
Trade name : PROTECTION EPOXY HAUTE RESISTANCE - COMPOSANT B
UFI : PRYE-U01R-H00S-0U4K
Product code : 505STB
Product group : HALF FINISHED

1.2. Relevant identified uses of the substance or mixture and uses advised against**1.2.1. Relevant identified uses**

Main use category : Professional use
Industrial/Professional use spec : For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet**Manufacturer**

Ressource
Rue de Mousselière
30133 Les Angles - FRANCE
T +33(0)490254245
contact@ressource-decoration.com - www.ressource-peintures.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre, Wolfson Unit	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0344 892 0111	

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects.

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS07

PROTECTION EPOXY HAUTE RESISTANCE - COMPOSANT B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Signal word (CLP)	: Warning
Contains	: 1,2-benzisothiazol-3(2H)-one; reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1); reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)
Hazard statements (CLP)	: H317 - May cause an allergic skin reaction. H319 - Causes serious eye irritation. H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P333+P313 - If skin irritation or rash occurs: Get medical advice/attention. P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)	(CAS-No.) 25068-38-6 (EC-No.) 500-033-5 (EC Index-No.) 603-074-00-8 (REACH-no) 01-2119456619-26	10 – 20	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
1-methoxy-2-propanol; monopropylene glycol methyl ether	(CAS-No.) 107-98-2 (EC-No.) 203-539-1 (EC Index-No.) 603-064-00-3 (REACH-no) 01-2119457435-35	1 – 5	Flam. Liq. 3, H226 STOT SE 3, H336
Benzyl alcohol	(CAS-No.) 100-51-6 (EC-No.) 202-859-9 (EC Index-No.) 603-057-00-5 (REACH-no) 01-2119492630-38	1 – 5	Acute Tox. 4 (Inhalation), H332 (ATE=11 mg/l/4h) Acute Tox. 4 (Oral), H302 (ATE=1230 mg/kg de poids corporel)
1,2-benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9 (EC Index-No.) 613-088-00-6	< 0,1	Acute Tox. 4 (Oral), H302 (ATE=597 mg/kg de poids corporel) Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400

PROTECTION EPOXY HAUTE RESISTANCE - COMPOSANT B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	(CAS-No.) 55965-84-9 (EC Index-No.) 613-167-00-5 (REACH-no) 01-2120764691-48	< 0,1	Acute Tox. 2 (Inhalation), H330 (ATE=0,33 mg/l/4h) Acute Tox. 2 (Dermal), H310 (ATE=87,12 mg/kg de poids corporel) Acute Tox. 3 (Oral), H301 (ATE=64 mg/kg de poids corporel) Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=100)
---	--	-------	--

Specific concentration limits:

Name	Product identifier	Specific concentration limits
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight \leq 700)	(CAS-No.) 25068-38-6 (EC-No.) 500-033-5 (EC Index-No.) 603-074-00-8 (REACH-no) 01-2119456619-26	($5 \leq C \leq 100$) Skin Irrit. 2, H315 ($5 \leq C \leq 100$) Eye Irrit. 2, H319
1,2-benzisothiazol-3(2H)-one	(CAS-No.) 2634-33-5 (EC-No.) 220-120-9 (EC Index-No.) 613-088-00-6	($0,05 \leq C \leq 100$) Skin Sens. 1, H317
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	(CAS-No.) 55965-84-9 (EC Index-No.) 613-167-00-5 (REACH-no) 01-2120764691-48	($0,0015 \leq C \leq 100$) Skin Sens. 1A, H317 ($0,06 \leq C < 0,6$) Eye Irrit. 2, H319 ($0,06 \leq C < 0,6$) Skin Irrit. 2, H315 ($0,6 \leq C \leq 100$) Eye Dam. 1, H318 ($0,6 \leq C \leq 100$) Skin Corr. 1C, H314

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

PROTECTION EPOXY HAUTE RESISTANCE - COMPOSANT B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Wear personal protective equipment.
Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)	
Austria - Occupational Exposure Limits	
Local name	5-Chlor-2-methyl-2,3-dihydroisothiazol-3-on und 2-Methyl-2,3-di-hydroisothiazol-3-on (Gemisch im Verhältnis 3:1)
MAK (OEL TWA)	0,05 mg/m ³
Remark (AT)	Sh,H

PROTECTION EPOXY HAUTE RESISTANCE - COMPOSANT B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: Not available
Odour	: Not available
Odour threshold	: Not available
Melting point	: Not applicable

PROTECTION EPOXY HAUTE RESISTANCE - COMPOSANT B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Freezing point	: Not available
Boiling point	: Not available
Flammability	: Not applicable
Explosive limits	: Not available
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Flash point	: Not available
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: > 7
Viscosity, kinematic	: Not available
Viscosity, dynamic	: 100 – 1000
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50 °C	: Not available
Density	: 1,061 g/cm ³
Relative density	: 1,061
Relative vapour density at 20 °C	: Not available
Particle size	: Not applicable
Particle size distribution	: Not applicable
Particle shape	: Not applicable
Particle aspect ratio	: Not applicable
Particle aggregation state	: Not applicable
Particle agglomeration state	: Not applicable
Particle specific surface area	: Not applicable
Particle dustiness	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : ≈ 0 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

PROTECTION EPOXY HAUTE RESISTANCE - COMPOSANT B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
LD50 oral rat	597 mg/kg
LD50 dermal rat	> 2000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	
LD50 oral rat	> 2000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg (OCDE 402)

Benzyl alcohol (100-51-6)	
LD50 oral rat	1230 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 4178 mg/m ³

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)	
LD50 oral rat	3739 mg/kg
LD50 dermal rabbit	13 g/kg
LC50 Inhalation - Rat	31,59 mg/l/4h
LC50 Inhalation - Rat [ppm]	15000 ppm/4h

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)	
LD50 oral rat	64 mg/kg
LD50 dermal rabbit	87,12 mg/kg
LC50 Inhalation - Rat	0,33 mg/l/4h
LC50 Inhalation - Rat (Dust/Mist)	0,33 mg/l/4h

Skin corrosion/irritation : Not classified
pH: > 7
Serious eye damage/irritation : Causes serious eye irritation.
pH: > 7
Respiratory or skin sensitisation : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)	
STOT-single exposure	May cause drowsiness or dizziness.

PROTECTION EPOXY HAUTE RESISTANCE - COMPOSANT B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

STOT-repeated exposure : Not classified

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	
LOAEL (oral, rat, 90 days)	50 mg/kg bodyweight/day (OCDE 408)
NOAEL (oral, rat, 90 days)	50 mg/kg bodyweight/day (OECD 408)

Aspiration hazard : Not classified

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Harmful to aquatic life with long lasting effects.

1,2-benzisothiazol-3(2H)-one (2634-33-5)	
LC50 - Fish [1]	0,74 mg/l 96 Hours (Oncorhynchus mykiss)
EC50 - Crustacea [1]	1,9 mg/l 96 Hours (Mysidopsis bahia)
EC50 - Crustacea [2]	1,5 mg/l 48 heures (Daphnia magna)
ErC50 algae	0,11 mg/l 72 Hours (Pseudokirchnerella subcapitata)
NOEC (acute)	0,15 mg/l 48 Hours (Scenedesmus acutus)

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (25068-38-6)	
LC50 - Fish [1]	1,3 mg/l (96h) (OECD 203)
EC50 - Crustacea [1]	1,7 mg/l (48h) (OECD 202)
ErC50 algae	9,4 mg/l (72h) (EPA CFR)
NOEC (chronic)	0,3 mg/l (21jours) (Daphnia magna) (OECD 211)

Benzyl alcohol (100-51-6)	
LC50 - Fish [1]	10 mg/l 96 Hours (Lepomis macrochirus)
EC50 - Crustacea [1]	230 mg/l 48 Hours (Daphnia magna) (OECD 202 method)
ErC50 algae	770 mg/l 72 Hours (Pseudokirchneriella subcapitata) (OECD 201 method)
NOEC (acute)	310 mg/l 72 Hours (Pseudokirchneriella subcapitata) (OECD 201 method)
NOEC (chronic)	51 mg/l 21 days (Daphnia magna) (OECD 202 method)

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)	
LC50 - Fish [1]	4600 mg/l 96 Hours (Leuciscus idus)
EC50 - Crustacea [1]	23300 mg/l 48 Hours
ErC50 algae	> 1000 mg/l 168 Hours

PROTECTION EPOXY HAUTE RESISTANCE - COMPOSANT B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (55965-84-9)	
LC50 - Fish [1]	0,19 mg/l 96 Hours (Oncorhynchus mykiss) (OECD 203 method)
LC50 - Fish [2]	0,28 mg/l (96h) (Lepomis macrochirus)
EC50 - Crustacea [1]	0,16 mg/l 48 Hours (Daphnia magna) (OECD 202 method)
ErC50 algae	0,027 mg/l 48 Hours (Pseudokirchnerella subcapitata) (OECD 201 method)
NOEC (acute)	0,0014 72 Hours (Skeletonema costatum) (OECD 201 method)
NOEC chronic fish	0,05 mg/l 14 days (Oncorhynchus mykiss) (OECD 203 method)
NOEC chronic crustacea	0,1 mg/l 21 days (Daphnia magna) (OECD 202 method)
NOEC chronic algae	0,0014 mg/l

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated

PROTECTION EPOXY HAUTE RESISTANCE - COMPOSANT B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

14.5. Environmental hazards

Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:	
Reference code	Applicable on
3.	Benzyl alcohol
3(b)	PROTECTION EPOXY HAUTE RESISTANCE - COMPOSANT B ; Benzyl alcohol

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

VOC content : ≈ 0 g/l

15.1.2. National regulations

France

Occupational diseases

Code	Description
RG 65	Eczematiform lesions of allergic mechanism
RG 66	Occupational rhinitis and asthma

Other information, restrictions and prohibition regulations : Classification according to directives 67/548/EEC and 1999/45/EC
VOC Directive 2004/42/EC - Decorative paints and varnishes
Labelling of building products or products used for wall or floor coatings and paints and varnishes concerning their emissions of volatile pollutants (Order of 19 April 2011)
Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV, Annex 1)
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed

PROTECTION EPOXY HAUTE RESISTANCE - COMPOSANT B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
LC50	Median lethal concentration
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
LD50	Median lethal dose
SDS	Safety Data Sheet
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
vPvB	Very Persistent and Very Bioaccumulative
STP	Sewage treatment plant
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
PBT	Persistent Bioaccumulative Toxic

Data sources : Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Other information : The working conditions of the user are not known to us, the information provided in this safety data sheet are based on the State of our knowledge and on both national and Community regulations. The mixture should not be used for other uses as those specified in section 1 without first obtaining prior written handling instructions. It is always the responsibility of the user to take all the necessary measures to meet the requirements of the laws and local regulations. The information provided in this safety data sheet should be considered a description of the safety requirements to this mixture and not as a guarantee of the properties of it.

The working conditions of the user are not known to us, the information provided in this safety data sheet are based on the State of our knowledge and on both national and Community regulations. The mixture should not be used for other uses as those specified in section 1 without first obtaining prior written handling instructions. It is always the responsibility of the user to take all the necessary measures to meet the requirements of the laws and local regulations. The information provided in this safety data sheet should be considered a description of the safety requirements to this mixture and not as a guarantee of the properties of it.

PROTECTION EPOXY HAUTE RESISTANCE - COMPOSANT B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.