

UNIVERSAL PRIMER

Penetrating and fixing primer for walls and ceilings (porous and chalky substrates).



RECOMMENDED USE

Indoors.

For vertical surfaces and ceilings, in all rooms.

Substrates: All standard building materials that have been properly primed. All very porous and powdery substrates. Water-based plaster and derivatives. Other kinds of plaster and derivatives. Adherent and properly prepared lime paints.

BENEFITS

- High-quality satin finish primer facilitates adhesion of all types of paint to all surfaces.
- The resin particles of this primer are extremely fine in aqueous dispersion giving this primer exceptional filling and fixating power.
- Nourishes and fixates flaky substrates.
- Microporous, unsaponifiable.
- Does not splatter.
- Does not leave streaks on woodwork.
- Excellent adhesion and hardening properties.
- Enriched with an anti-flash rust agent so as not to rust nail heads.

SURFACE PREPARATION

All surfaces must be perfectly cleaned, dusted and dry. Treat moldy surfaces with a fungicide product. For previously waxed floors, wash thoroughly to remove all the remaining wax. Remove any old lacquer or varnish with fine sanding paper. Remove any old wallpaper before repainting.

New Plaster: Once completely dry, sand with very fine sanding paper and dust again.

Smooth or troweled cement plaster: Brush with a hard brush and dust. Apply 1 to 2 coats of water-based plaster according to your desired finish. Once completely dry, sand with very fine sanding paper and dust.

Wood and wood derivatives: Sand with fine sanding paper and brush with a hard brush. Use a cellulose thinner on any greasy or resinous exotic wood. Fill any holes with putty. Sand with fine sanding paper and dust. Apply 2 coats of smoothing plaster (except around windows and patio doors). Once completely dry, sand with very fine sanding paper and dust.

Previously painted or wallpapered surfaces: Check the adhesion of any previous layers of paint. Strip the surface if the paint is coming off entirely. If it's only coming off in small areas, simply scrape it off. Wash off any old whitewash and glue with water. Wash any old paint and rinse with clear water. Always remove the polish from smooth or glossy surfaces.

Application tools: Apply using either a 10mm microfibre roller, an airless sprayer or a pneumatic sprayer.

APPLICATION

Apply one coat using a brush or a roller, diluting with approx. 5% water.

With an airless or traditional paint sprayer and depending on the type of equipment used, the primer may need to be diluted with 10 to 20% water. Test the dilution on a piece of cardboard or an inconspicuous area to obtain the best dilution.

GENERAL INFORMATION

Appearance: Velvet.

Coverage: 10-12m²/L depending on the porosity of the surface.

Drying time: 30mins (dry to the touch).

Second coat: 4 to 24h depending on the porosity of the surface: a porous surface will dry faster.

Solid content: 54% (+/-2%) in weight, 38% (+/-2%) in volume.

Density: 1.36g/cm³ (+/-0.05).

How to clean your equipment: Water.

Packaging: 0.5L, 1L, 2.5L, 5L and 10L.

Storage: 1 year in its original unopened packaging. Keep away from frost.

HANDLE WITH CARE

Use in temperatures between +8°C and + 35°C. Do not use when relative humidity reaches more than 70%.

REGULATORY INFORMATION

AFNOR Classification: Family I - Classe 7b2.

VOC⁽¹⁾: The 2010 EU limit value for this product (cat A/g) is 30g/L. This product contains maximum 8g/L VOC.

Safety: Refer to the Safety Data Sheet (SDS). Complies with current legislation.

⁽¹⁾ Volatile Organic Compounds: Directive 2004/42/EC.

* Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions).