

WATER-BASED CEILING MATTE

Matte insulating alkyd-based emulsion for ceilings.



RECOMMENDED USE

Indoors.

On ceilings. In all indoor rooms.

Substrates: All standard building materials that have been properly primed.

BENEFITS

- Matte insulating alkyd-based emulsion for ceilings.
- Highly covering and sealing.
- Bright white.
- Does not leave streaks, marks or lines.
- Wet abrasion resistance.
- Class 2⁽²⁾ (after 28 days of drying).
- Microporous. Little surface preparation needed.
- Protects against stains (nicotine, soot).

SURFACE PREPARATION

The surface must be perfectly cleaned, dusted and dry. Apply the appropriate primer and/or undercoat for the substrate.

Powdery, gelatinous, whitewashed or limewashed surfaces: No need to wash the surface if it is adherent and not greasy. If not, degrease appropriately and apply our Universal Primer.

Plasterboard, plaster derivatives and other porous surfaces: Apply our Universal Primer.

Old paint in good condition (not very porous surfaces): Sand and dust. Wash and rinse if necessary. Apply our Undercoat for Light or Dark Colours, or our Undercoat for Regular Work.

Application tools: Apply using a special acrylic brush, a 10mm roller, a 12mm non-drip roller, an airless or pneumatic sprayer.

APPLICATION

Once the undercoat is completely dry, apply two coats of Water-based Ceiling Matte using a brush or roller. The second coat can be applied after 4 hours of drying, except if the surface being painted is stained in any way in which case, allow 24 hours for drying. Dilute with a maximum of 5% water.

With an airless or traditional paint sprayer and depending on the type of equipment used, the paint may need to be diluted with 10 to 20% water. The dilution will depend on the porosity of the surface. We recommend testing the dilution on a small area to determine the right percentage (the paint should not be too thin and it should glide easily over the surface).

GENERAL INFORMATION

Appearance: Deep Matte.

Gloss: 2 to 4GU at 60° < 2GU at 85°.

Coverage: 11-13m²/L per coat depending on your choice of equipment and dilution.

GENERAL INFORMATION

Drying time: 3-4h (dry to the touch).

Second coat: 4-5h. On stained surfaces: 24h (depending on the temperature and air humidity).

Solid content: 66% in weight (+/-2%), 47% in volume (+/-2%).

Density: 1.57g/cm³ (+/-0.05%) in white.

How to clean your equipment: Water.

Packaging: 2.5L, 5L and 12L.

Storage: 1 year in its original unopened packaging. Keep away from frost.

HANDLE WITH CARE

Use in temperatures between +8°C and + 35°C. Do not use when relative humidity reaches more than 70%.

REGULATORY INFORMATION

AFNOR Classification: Family I - Classe 4a/7b2.

VOC⁽¹⁾: The 2010 EU limit value for this product (cat A/a) is 30g/L. This product contains maximum 15g/L VOC.

Safety: Refer to the safety Data Sheet (SDS). Complies with current legislation.

⁽¹⁾ Volatile Organic Compounds: Directive 2004/42/EC.

⁽²⁾ According to ISO 11998 and EN 13300, the paint film is resistant to cleaning with a sponge, using gentle household products. Take care as washing may leave a sheen on some strong colours.

* Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions).