

## WALLPAPER VARNISH

Ressource wallpaper protection.



RECOMMENDED USE

Indoors.

For vertical surfaces. In all indoor rooms.

Substrates: Ressource wallpapers. For any other brands of wallpaper, test before using.

**BENEFITS** 

- Matte and highly transparent appearance.

- Respects the matte appearance of Ressource wallpapers.

- Protects the wallpaper from water spillage.

- Allows delicate maintenance.

- Stops stains from penetrating the paper, if you clean the surface quickly.

SURFACE PREPARATION

Gently dust the wallpaper with a microfiber cloth without exerting any pressure on the paper.

<u>Application tools</u>: Apply using a 5mm microfibre roller.

**APPLICATION** 

Apply 1 or 2 coats of Wallpaper Varnish with a 5mm roller. Examine the whole surface in grazing light to ensure there are no gaps. Make crisscrossing movements so as to obtain an even layer of varnish.

During application, the varnish should be translucid before drying. If there are any white blotches, keep smoothing the varnish until they disappear.

MAINTENANCE

The varnish reduces the wallpaper's sensitivity to water.

Keep the surface clean by gently washing it with a damp sponge.

The varnish prevents stains from penetrating immediately. In the event of splashes on the wallpaper, we recommend you to quickly blot the surface.

GENERAL INFORMATION

 $\textbf{Finish} \colon \mathsf{Matte}.$ 

**Gloss**: 3 to 4GU at 60°.

Coverage: 15-16m<sup>2</sup>/L per coat.

Drying time: 1h (dry to the touch).

Second coat: Approx. 4h (depending on the temperature and air humidity).

Solid content: 17% in weight, 15.2% in volume.

Density: 1.02g/cm<sup>3</sup>.

## GENERAL INFORMATION

How to clean your equipment: Water.

Packaging: 0.5L.

Storage: 1 year in its original unopened packaging. Keep away from frost.

## HANDLE WITH CARE

Use in temperatures between +5°C and +30°C. Do not use when relative humidity reaches more than 75%.

## REGULATORY INFORMATION

AFNOR Classification: Family I - Class 6a.

VOC(1): The 2010 EU limit value for this product (cat A/e) is 130g/L.

This product contains maximum 98g/L VOC.

Safety: Refer to the safety Data Sheet (SDS). Complies with current legislation.

TDS No. 972 Edition 23 September 2020. This Technical Data Sheet cancels and replaces the previous editions for the same product. As techniques evolve constantly, it is the sole responsibility of our customers to check with our services - before use - that this Technical Data Sheet is the most recent edition.

Document available on our website www.ressource-peintures.com

<sup>(1)</sup> Volatile Organic Compounds: Directive 2004/42/EC.

Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions)