

## UNDERCOAT FOR DARK COLORS

Smoothes and regulates absorption on slightly porous and non-powdery substrates.



### RECOMMENDED USE

#### Indoors.

On vertical and horizontal surfaces (floors and ceilings). In all indoor spaces.

Substrates: All standard slightly porous but non-powdery building materials that have been properly primed. If you are painting ferrous materials, apply a Rustproof Primer first.

### BENEFITS

- Tintable undercoat for strong, bright or dark full tone shades (see list of available shades in store).
- Gives the finish great opacity, regulates porosity and absorption of any surface.
- Facilitates adhesion of the desired finish and gives a clean and long-lasting result.
- High resistance to alkalinity. Microporous. Does not yellow. Quick to dry. Adheres well to previous sanded paintwork.

### SURFACE PREPARATION

The surface must be perfectly cleaned, dusted and dry. Apply the appropriate primer and/or undercoat for the substrate. For porous, powdery and flaky surfaces, use our Universal Primer.

**Plasterboard, old paint in good condition (slightly porous surfaces):** Sand and dust. Wash and rinse if necessary.

**Application tools:** Apply using a special acrylic brush, a 10mm microstar roller, an airless or pneumatic sprayer.

### APPLICATION

Apply one coat of Undercoat for Dark Colors in full Tones, diluted with 5-10% water depending on the porosity of the surface. For non absorbent surfaces, do not dilute.

With an airless or traditional paint sprayer and depending on the type of equipment used, the paint may need to be diluted with 15 to 30% water. Test the dilution on a piece of cardboard or an inconspicuous area to obtain the best dilution, which will depend on the porosity of the substrate. We recommend testing the dilution on a small area to determine the right percentage (the paint should not be too thin and it should glide easily over the surface).

### GENERAL INFORMATION

**Finish:** Matte.

**Coverage:** 10-12m<sup>2</sup>/L per coat depending on your choice of equipment and dilution.

**Drying time:** 30mins (dry to the touch).

**Second coat:** Approx. 4-6h (depending on the temperature and air humidity).

**Solid content:** 57% in weight, 44% in volume.

**Density:** 1.30g/cm<sup>3</sup>.

**How to clean your equipment:** Water.

**Packaging:** 0.5L, 1L, 2.5L, 5L and 10L.

**Storage:** 1 year in its original unopened packaging. Keep away from frost.

**HANDLE WITH CARE**

Use in temperatures between +8°C and +35°C. Do not use when relative humidity reaches more than 70%.

**REGULATORY  
INFORMATION**

**AFNOR Classification:** Family I - Class 7b2/7a2.

**VOC<sup>(1)</sup>:** The 2010 EU limit value for this product (cat A/g) is 30g/L.  
This product contains maximum 5g/L VOC.

**Safety:** Refer to the safety Data Sheet (SDS). Complies with current legislation.

<sup>(1)</sup> Volatile Organic Compounds: Directive 2004/42/EC.

\* Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions).

*TDS No. 952 Edition 20 March 2020. This Technical Data Sheet cancels and replaces the previous editions for the same product. As techniques evolve constantly, it is the sole responsibility of our customers to check with our services - before use - that this Technical Data Sheet is the most recent edition.*

**Document available on our website [www.ressource-peintures.com](http://www.ressource-peintures.com)**