

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010
Issue date: 11/05/2018 Revision date: 07/10/2021 Supersedes version of: 07/10/2021 Version: 1.2

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : IMPRESSION EXTERIEUR BOIS
Product code : 316ST
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : For professional use only
Use of the substance/mixture : Suitable paint for indoor/outdoor woodwork.

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Ressource
Rue de Mousselière
FR- 30133 Les Angles
FRANCE
T +33(0)490254245
contact@ressource-decoration.com - www.ressource-peintures.com

1.4. Emergency telephone number

| Country | Organisation/Company | Address | Emergency number | Comment |
|----------------|---|---|-------------------|---|
| France | ORFILA | | +33 1 45 42 59 59 | This number provides contact details for all French Poison Control centers. These poison and toxicovigilance centers provide free medical assistance (excluding call costs), 24 hours a day, 7 days a week. |
| United Kingdom | National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre | 16/17 Framlington Place Newcastle-upon-Tyne NE2 4AB | 0344 892 0111 | Only for healthcare professionals |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Carcinogenicity Not classified
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour.

IMPRESSION EXTERIEUR BOIS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

Signal word (CLP) : Warning
Hazard statements (CLP) : H226 - Flammable liquid and vapour.
Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
EUH-statements : EUH210 - Safety data sheet available on request.
EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
EUH066 - Repeated exposure may cause skin dryness or cracking.
EUH208 - Contains 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime(96-29-7). May produce an allergic reaction.
Extra phrases : For professional users only.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|--|---|--------------------|--|
| Titanium dioxide | CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-002 REACH-no: 01-2119489379-17 | 8,11478 – 20,46118 | Carc. 2, H351 |
| Hydrocarbons, C9-C11, isoalkanes, cyclics, < 2% aromatics | CAS-No.: 1174522-20-3 EC-No.: 919-857-5 REACH-no: 01-2119463258-33 | 4,5 – 12,223 | Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 |
| Calcium carbonate | CAS-No.: 471-34-1 EC-No.: 207-439-9 REACH-no: 01-2119486795-18 | 2,2956 – 3,71122 | Acute Tox. 4 (Inhalation:dust,mist), H332 |
| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics | EC-No.: 918-481-9 REACH-no: 01-2119457273-39 | 1 – 2,893 | Asp. Tox. 1, H304 |
| Isotridecylalcohol, ethoxylated, phosphated, compd. with N,N-dimethylcyclohexanamine | CAS-No.: 164383-18-0 | 0 – 1,63 | Skin Irrit. 2, H315 Eye Irrit. 2, H319 Aquatic Chronic 2, H411 |

IMPRESSION EXTERIEUR BOIS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

| Name | Product identifier | % | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|---|---|-----------|---|
| 2-ethylhexanoic acid, zirconium salt | CAS-No.: 22464-99-9 EC-No.: 245-018-1 REACH-no: 01-2119979088-21 | ≤ 0,45435 | Repr. 2, H361d |
| 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime | CAS-No.: 96-29-7 EC-No.: 202-496-6 EC Index-No.: 616-014-00-0 REACH-no: 01-2119539477-28 | 0 – 0,282 | Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation:vapour), H332 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351 |
| dipropylene glycol methyl ether substance with a Community workplace exposure limit | CAS-No.: 34590-94-8 EC-No.: 252-104-2 REACH-no: 01-2119450011-60 | ≤ 0,12187 | Not classified |

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|--|
| First-aid measures general | : In all cases of doubt, or when symptoms persist, seek medical attention. |
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. |
| First-aid measures after skin contact | : Rinse skin with water/shower. Take off immediately all contaminated clothing. |
| First-aid measures after eye contact | : Continue to rinse eye with clean water for 20-30 minutes, retracting eyelids often. Rinse eyes with water as a precaution. |
| First-aid measures after ingestion | : IF SWALLOWED : Rinse mouth. Do NOT induce vomiting. Immediately call a POISON CENTER or doctor. Specific treatment. Call a poison center or a doctor if you feel unwell. |

4.2. Most important symptoms and effects, both acute and delayed

| | |
|-------------------------------------|--|
| Symptoms/effects | : May cause drowsiness or dizziness. |
| Symptoms/effects after skin contact | : Cracking of the skin. Slight irritation. Repeated exposure may cause skin dryness or cracking. |
| Symptoms/effects after eye contact | : Eye irritation. |
| Symptoms/effects after ingestion | : Ingestion may cause nausea and vomiting. |

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

| | |
|--|---|
| Fire hazard | : Flammable liquid and vapour. |
| Hazardous decomposition products in case of fire | : Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide. |

5.3. Advice for firefighters

Precautionary measures fire : Eliminate all ignition sources if safe to do so.

IMPRESSION EXTERIEUR BOIS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

| | |
|--------------------------------|---|
| Firefighting instructions | : Cool adjacent tanks / containers / drums with water jet. Do not enter fire area without proper protective equipment, including respiratory protection. Prevent fire fighting water from entering the environment. Fight fire from a safe distance or use hoses with support or cannon engine. |
| Protection during firefighting | : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing. |
| Other information | : On exposure to high temperature, may decompose, releasing toxic gases. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|------------------|--|
| General measures | : Remove ignition sources. Clean up any spills as soon as possible, using an absorbent material to collect it. Avoid contact with skin and eyes. |
|------------------|--|

6.1.1. For non-emergency personnel

| | |
|----------------------|---|
| Protective equipment | : Wear recommended personal protective equipment. |
| Emergency procedures | : Ventilate spillage area. No open flames, no sparks, and no smoking. |

6.1.2. For emergency responders

| | |
|----------------------|---|
| Protective equipment | : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection". |
|----------------------|---|

6.2. Environmental precautions

Avoid release to the environment. Liquid spill: take up in dry sand/earth/vermiculite. Cover spill with non combustible material, e.g.: sand, earth, vermiculite.

6.3. Methods and material for containment and cleaning up

| | |
|-------------------------|---|
| For containment | : Stop leak without risks if possible. Consult an expert on waste disposal or treatment. |
| Methods for cleaning up | : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters. |
| Other information | : Dispose of materials or solid residues at an authorized site. |

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|-----------------------------------|---|
| Additional hazards when processed | : Do not allow contact with water. Always wash hands after handling the product. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| Precautions for safe handling | : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. |
| Hygiene measures | : Do not eat, drink or smoke when using this product. Always wash hands after handling the product. |

7.2. Conditions for safe storage, including any incompatibilities

| | |
|------------------------------|---|
| Technical measures | : Ground/bond container and receiving equipment. |
| Storage conditions | : Store in a well-ventilated place. Keep cool. Keep container tightly closed. |
| Heat and ignition sources | : Keep away from open flames, hot surfaces and sources of ignition. |
| Information on mixed storage | : Keep out of reach of children. |
| Storage area | : Store in a well-ventilated place. Store away from heat. |
| Special rules on packaging | : Keep only in original container. Store in a closed container. |
| Packaging materials | : Keep only in the original container in a cool, well-ventilated place away from combustible materials. |

IMPRESSION EXTERIEUR BOIS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

| Calcium carbonate (471-34-1) | |
|--|--|
| France - Occupational Exposure Limits | |
| Local name | Calcium (carbonate de) |
| VME (OEL TWA) | 10 mg/m ³ |
| Latvia - Occupational Exposure Limits | |
| Local name | Kalcijakarbonāts |
| OEL TWA | 6 mg/m ³ |
| Poland - Occupational Exposure Limits | |
| Local name | Węglan wapnia pyły 10) |
| NDS (OEL TWA) | 10 mg/m ³ |
| Portugal - Occupational Exposure Limits | |
| Local name | Carbonato de cálcio |
| OEL TWA | 10 mg/m ³ |
| Titanium dioxide (13463-67-7) | |
| Austria - Occupational Exposure Limits | |
| Local name | Titandioxid (Alveolarstaub) |
| MAK (OEL TWA) | 5 mg/m ³ |
| MAK (OEL STEL) | 10 mg/m ³ |
| Belgium - Occupational Exposure Limits | |
| Local name | Titane (dioxyde de) |
| OEL TWA | 10 mg/m ³ |
| Bulgaria - Occupational Exposure Limits | |
| Local name | Титанов диоксид, респирабилен прах |
| OEL TWA | 10 mg/m ³ |
| Croatia - Occupational Exposure Limits | |
| Local name | Titanov dioksid |
| GVI (OEL TWA) [1] | 10 mg/m ³ inhalable dust 4 mg/m ³ respirable dust |
| Denmark - Occupational Exposure Limits | |
| Local name | Titandioxid, beregnet som Ti |
| OEL TWA [1] | 6 mg/m ³ |
| Estonia - Occupational Exposure Limits | |
| Local name | Titaanoksiid |
| OEL TWA | 5 mg/m ³ |

IMPRESSION EXTERIEUR BOIS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

| Titanium dioxide (13463-67-7) | |
|--|--|
| France - Occupational Exposure Limits | |
| Local name | Titane (dioxyde de),en Ti |
| VME (OEL TWA) | 10 mg/m ³ |
| Greece - Occupational Exposure Limits | |
| OEL TWA | 10 mg/m ³ |
| Latvia - Occupational Exposure Limits | |
| Local name | Titānadioksīds |
| OEL TWA | 10 mg/m ³ |
| Lithuania - Occupational Exposure Limits | |
| Local name | Titano dioksidas |
| IPRV (OEL TWA) | 5 mg/m ³ |
| Portugal - Occupational Exposure Limits | |
| Local name | Dióxido de titânio |
| OEL TWA | 10 mg/m ³ |
| Spain - Occupational Exposure Limits | |
| Local name | Dióxido de titanio |
| VLA-ED (OEL TWA) [1] | 10 mg/m ³ |
| Sweden - Occupational Exposure Limits | |
| Local name | Titanium dioxide total dust |
| NGV (OEL TWA) [ppm] | 5 ppm |
| United Kingdom - Occupational Exposure Limits | |
| Local name | Titanium dioxide |
| WEL TWA (OEL TWA) [1] | 4 mg/m ³ respirable 10 mg/m ³ total inhalable |
| Iceland - Occupational Exposure Limits | |
| Local name | Títandíoxíð, sem Ti |
| OEL TWA | 6 mg/m ³ |
| Norway - Occupational Exposure Limits | |
| Local name | Titandioksid |
| Grønseverdi (OEL TWA) [1] | 5 mg/m ³ |
| Switzerland - Occupational Exposure Limits | |
| Local name | Dioxyde de titane |
| MAK (OEL TWA) [1] | 3 mg/m ³ |
| USA - ACGIH - Occupational Exposure Limits | |
| Local name | Titanium dioxide |
| ACGIH OEL TWA | 1 mg/m ³ |
| Remark (ACGIH) | LRT irr; A3 |

IMPRESSION EXTERIEUR BOIS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

| dipropylene glycol methyl ether (34590-94-8) | |
|---|--|
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| Local name | (2-Methoxymethylethoxy)-propanol |
| IOEL TWA | 308 mg/m ³ |
| IOEL TWA [ppm] | 50 ppm |
| Remark | Skin |
| Austria - Occupational Exposure Limits | |
| Local name | Dipropylenglykolmonomethylether (Isomerengemisch) |
| MAK (OEL TWA) | 307 mg/m ³ |
| MAK (OEL TWA) [ppm] | 50 ppm |
| MAK (OEL STEL) | 614 mg/m ³ |
| MAK (OEL STEL) [ppm] | 100 ppm |
| Remark | H |
| Belgium - Occupational Exposure Limits | |
| Local name | Dipropylèneglycolmonométhyléther |
| OEL TWA | 308 mg/m ³ |
| OEL TWA [ppm] | 50 ppm |
| Remark | D |
| Bulgaria - Occupational Exposure Limits | |
| Local name | пропанол• |
| OEL TWA | 308 mg/m ³ |
| Croatia - Occupational Exposure Limits | |
| Local name | (2-Metoksimetiletoksi)– – propanol |
| GVI (OEL TWA) [1] | 308 mg/m ³ |
| GVI (OEL TWA) [2] | 50 ppm |
| Remark | K, EU* |
| Czech Republic - Occupational Exposure Limits | |
| Local name | propanol(2-Methoxymethylethoxy)-(technická sm s isomer) |
| PEL (OEL TWA) | 270 mg/m ³ |
| PEL (OEL TWA) [ppm] | 44,6 ppm |
| NPK-P (OEL C) | 550 mg/m ³ |
| NPK-P (OEL C) [ppm] | 90,8 ppm |
| Denmark - Occupational Exposure Limits | |
| Local name | Dipropylenglycolmethylether (1994) |
| OEL TWA [1] | 300 mg/m ³ |
| OEL TWA [2] | 50 ppm |
| Estonia - Occupational Exposure Limits | |
| Local name | Dipropüleenglükooli monometüüleeter (2-etoksümetüületoksü)-propanool |
| OEL TWA | 308 mg/m ³ |
| OEL TWA [ppm] | 50 ppm |

IMPRESSION EXTERIEUR BOIS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

| dipropylene glycol methyl ether (34590-94-8) | |
|--|--|
| Finland - Occupational Exposure Limits | |
| Local name | (2-Metoksimetyylietoksi)-propanoli |
| HTP (OEL TWA) [1] | 310 mg/m ³ |
| HTP (OEL TWA) [2] | 50 ppm |
| France - Occupational Exposure Limits | |
| Local name | (2-méthoxyméthylethoxy)-propanol |
| VME (OEL TWA) | 308 mg/m ³ |
| VME (OEL TWA) [ppm] | 50 ppm |
| Germany - Occupational Exposure Limits (TRGS 900) | |
| Local name | (2-Methoxymethylethoxy)propanol(Isomerengemisch) |
| AGW (OEL TWA) [1] | 310 mg/m ³ |
| AGW (OEL TWA) [2] | 50 ppm |
| Remark | DFG,EU |
| Greece - Occupational Exposure Limits | |
| OEL TWA | 600 mg/m ³ |
| OEL TWA [ppm] | 100 ppm |
| OEL STEL | 900 mg/m ³ |
| OEL STEL [ppm] | 150 ppm |
| Hungary - Occupational Exposure Limits | |
| Local name | (2-METOXIMETILETOXI)-PROPANOL (Dipropilēnglikol-monometil-éter) |
| AK (OEL TWA) | 308 mg/m ³ |
| CK (OEL STEL) | 308 mg/m ³ |
| Ireland - Occupational Exposure Limits | |
| Local name | (2-Methoxymethylethoxy)-l-propanol |
| OEL TWA [1] | 308 mg/m ³ |
| OEL TWA [2] | 50 ppm |
| Italy - Occupational Exposure Limits | |
| Local name | (2-Metossimetilotossi)-propanolo |
| OEL TWA | 308 mg/m ³ |
| OEL TWA [ppm] | 50 ppm |
| Latvia - Occupational Exposure Limits | |
| Local name | Metoksiropoksi propanols (dipropilēnglikola monometilēteris,DPM) |
| OEL TWA | 308 mg/m ³ |
| OEL TWA [ppm] | 50 ppm |
| Lithuania - Occupational Exposure Limits | |
| Local name | 2-(2-metoksiropoksi)-propanolis (2-etoksimetiletoksi)-propanolis, dipropilēnglikolio monometilēteris |
| IPRV (OEL TWA) | 300 mg/m ³ |
| IPRV (OEL TWA) [ppm] | 50 ppm |

IMPRESSION EXTERIEUR BOIS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

| dipropylene glycol methyl ether (34590-94-8) | |
|---|---|
| TPRV (OEL STEL) | 450 mg/m ³ |
| TPRV (OEL STEL) [ppm] | 75 ppm |
| Malta - Occupational Exposure Limits | |
| Local name | (2-Methoxymethylethoxy)-propanol |
| OEL TWA | 308 mg/m ³ |
| OEL TWA [ppm] | 50 ppm |
| Netherlands - Occupational Exposure Limits | |
| Local name | Dipropyleenglycolmethylether |
| TGG-8u (OEL TWA) | 300 mg/m ³ |
| Poland - Occupational Exposure Limits | |
| Local name | (2-Metoksymetyloetoksy)propanol |
| NDS (OEL TWA) | 240 mg/m ³ |
| NDSch (OEL STEL) | 480 mg/m ³ |
| Portugal - Occupational Exposure Limits | |
| Local name | 2-Metoximetiletoxiopropanol (DPGME) |
| OEL TWA [ppm] | 100 ppm |
| OEL STEL [ppm] | 150 ppm |
| Romania - Occupational Exposure Limits | |
| Local name | (2-metoximetiletoxi)-propanol |
| OEL TWA | 308 mg/m ³ |
| OEL TWA [ppm] | 50 ppm |
| Slovenia - Occupational Exposure Limits | |
| Local name | (2-metoksimetiletoksi)propanol (mešanica izomer) |
| OEL TWA | 308 mg/m ³ |
| OEL TWA [ppm] | 50 ppm |
| Spain - Occupational Exposure Limits | |
| Local name | Éter metílico de dipropilenglicol |
| VLA-ED (OEL TWA) [1] | 308 mg/m ³ |
| VLA-ED (OEL TWA) [2] | 50 ppm |
| Remark | Vía dérmica: (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante. Para más información véase el Apartado 5 de este documento.), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país.) |
| Sweden - Occupational Exposure Limits | |
| Local name | Dipropylene glycol monomethyl ether |

IMPRESSION EXTERIEUR BOIS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

| dipropylene glycol methyl ether (34590-94-8) | |
|---|---|
| NGV (OEL TWA) | 300 mg/m ³ |
| NGV (OEL TWA) [ppm] | 50 ppm |
| KTV (OEL STEL) | 450 mg/m ³ |
| KTV (OEL STEL) [ppm] | 75 ppm |
| United Kingdom - Occupational Exposure Limits | |
| Local name | (2-methoxymethylethoxy) propanol |
| WEL TWA (OEL TWA) [1] | 308 mg/m ³ |
| WEL TWA (OEL TWA) [2] | 50 ppm |
| Remark | Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity) |
| Norway - Occupational Exposure Limits | |
| Local name | (2-Metoksymetyletoksy)-propanol |
| Grønseverdi (OEL TWA) [1] | 300 mg/m ³ |
| Grønseverdi (OEL TWA) [2] | 50 ppm |
| Switzerland - Occupational Exposure Limits | |
| Local name | Oxyde de dipropylèneglycolméthyle (mélange d'isomères) |
| MAK (OEL TWA) [1] | 300 mg/m ³ |
| MAK (OEL TWA) [2] | 50 ppm |
| KZGW (OEL STEL) | 300 mg/m ³ |
| KZGW (OEL STEL) [ppm] | 50 ppm |
| Remark | 15 min |

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Protective clothing. Wear gas mask if conc. in air >. Safety glasses. Gloves.

Personal protective equipment symbol(s):



IMPRESSION EXTERIEUR BOIS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Consumer exposure controls:

Avoid contact during pregnancy/while nursing. The substance is not classified for human health hazards or for environment effects and it is not PBT or vPvB so that no exposure assessment or risk characterisation is required. For tasks where the intervention of workers is required, the substance must be handled in accordance with good industrial hygiene and safety procedures.

Other information:

Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|--------------------------------|
| Physical state | : Liquid |
| Colour | : white. |
| Odour | : Not available |
| Odour threshold | : Not available |
| Melting point | : Not applicable |
| Freezing point | : Not available |
| Boiling point | : Not available |
| Flammability | : Flammable liquid and vapour. |
| Explosive limits | : Not available |
| Lower explosion limit | : Not available |
| Upper explosion limit | : Not available |
| Flash point | : ≈ 48 °C |
| Auto-ignition temperature | : Not available |
| Decomposition temperature | : Not available |
| pH | : > 7 |
| Viscosity, kinematic | : Not available |
| Viscosity, dynamic | : 500 – 2000 cP |
| Solubility | : Not available |
| Partition coefficient n-octanol/water (Log Kow) | : Not available |
| Vapour pressure | : Not available |
| Vapour pressure at 50°C | : < 1,1 bar |
| Density | : 1,416 g/cm ³ |
| Relative density | : < 1 |
| Relative vapour density at 20°C | : Not available |
| Particle characteristics | : Not applicable |

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

IMPRESSION EXTERIEUR BOIS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

9.2.2. Other safety characteristics

VOC content : < 300 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, nitrogen oxides (NOx).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

| Isotridecylalcohol, ethoxylated, phosphated, compd. with N,N-dimethylcyclohexanamine (164383-18-0) | |
|---|--------------------------------|
| LD50 oral rat | > 2500 mg/kg |
| 2-ethylhexanoic acid, zirconium salt (22464-99-9) | |
| LD50 oral rat | > 2000 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| Calcium carbonate (471-34-1) | |
| LD50 oral rat | 6450 mg/kg |
| LD50 dermal rat | > 2000 mg/kg (OECD 402) |
| LC50 Inhalation - Rat | > 3 mg/l/4h |
| 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (96-29-7) | |
| LD50 oral rat | ≈ 900 mg/kg |
| LD50 dermal rat | ≈ 1000 mg/kg |
| LC50 Inhalation - Rat | ≈ 13,2 mg/l |
| Hydrocarbons, C9-C11, isoalkanes, cyclics, < 2% aromatics (1174522-20-3) | |
| LD50 oral rat | > 5000 mg/kg (OECD 401 method) |
| LD50 dermal rat | > 5000 mg/kg (OECD 402 method) |

IMPRESSION EXTERIEUR BOIS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

| Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics | |
|---|--|
| LD50 oral rat | > 5000 mg/kg (OECD 401 method) |
| LD50 dermal rabbit | > 5000 mg/kg (OECD 402 method) |
| LC50 Inhalation - Rat | > 4951 mg/m ³ (OECD 403 method) |

| Titanium dioxide (13463-67-7) | |
|-------------------------------|----------------|
| LD50 oral rat | > 5000 mg/kg |
| LC50 Inhalation - Rat | > 6,82 mg/l/4h |

| | |
|-----------------------------------|-----------------------------|
| Skin corrosion/irritation | : Not classified pH: > 7 |
| Serious eye damage/irritation | : Not classified pH: > 7 |
| Respiratory or skin sensitisation | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified. |
| Reproductive toxicity | : Not classified |
| STOT-single exposure | : Not classified |

| Hydrocarbons, C9-C11, isoalkanes, cyclics, < 2% aromatics (1174522-20-3) | |
|--|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |

| | |
|------------------------|------------------|
| STOT-repeated exposure | : Not classified |
| Aspiration hazard | : Not classified |

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

| | |
|---|---|
| Ecology - general | : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. |
| Hazardous to the aquatic environment, short-term (acute) | : Not classified |
| Hazardous to the aquatic environment, long-term (chronic) | : Not classified |

| Isotridecylalcohol, ethoxylated, phosphated, compd. with N,N-dimethylcyclohexanamine (164383-18-0) | |
|--|-------------|
| LC50 - Fish [1] | 1 – 10 mg/l |

| 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (96-29-7) | |
|--|---------------------------------------|
| LC50 - Fish [1] | > 100 mg/l 96 Hours (Oryzias latipes) |
| EC50 - Crustacea [1] | 201 mg/l 48 Hours (Daphnia magna) |
| ErC50 algae | 11,8 mg/l 72 Hours |

| Hydrocarbons, C9-C11, isoalkanes, cyclics, < 2% aromatics (1174522-20-3) | |
|--|--|
| LC50 - Fish [1] | > 1000 mg/l 96 Hours (Onchorhynchus mykiss) (OECD 203 method) |
| EC50 - Crustacea [1] | > 1000 mg/l 48 Hours (Daphnia magna) (OECD 202 method) |
| ErC50 algae | > 1000 mg/l 72 Hours (Scenedesmus subspicatus) (OECD 201 method) |

| Titanium dioxide (13463-67-7) | |
|-------------------------------|--|
| LC50 - Fish [1] | > 1000 mg/l 96 Hours (Fundulus heteroclitus) |

IMPRESSION EXTERIEUR BOIS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Titanium dioxide (13463-67-7)

| | |
|----------------------|--------------------------------------|
| EC50 - Crustacea [1] | > 1000 mg/l 48 Hours (Daphnia magna) |
|----------------------|--------------------------------------|

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

| | |
|--|--|
| Regional legislation (waste) | : Disposal must be done according to official regulations. |
| Waste treatment methods | : Dispose of contents/container in accordance with licensed collector's sorting instructions. |
| Sewage disposal recommendations | : Disposal must be done according to official regulations. |
| Product/Packaging disposal recommendations | : Avoid release to the environment. Discharging into rivers and drains is forbidden. Dispose in a safe manner in accordance with local/national regulations. |
| Additional information | : Flammable vapours may accumulate in the container. |
| Ecology - waste materials | : Avoid release to the environment. |
| European List of Waste (LoW) code | : 08 01 12 - waste paint and varnish other than those mentioned in 08 01 11 |

SECTION 14: Transport information



In accordance with ADR / IMDG / IATA / ADN / RID

| ADR | IMDG | IATA | ADN | RID |
|---|--|--|---------------|---------------|
| 14.1. UN number or ID number | | | | |
| UN 1263 | UN 1263 | UN 1263 | Not regulated | Not regulated |
| 14.2. UN proper shipping name | | | | |
| PAINT (MIXTURE ; EXTERIEUR BOIS MAT VELOUTE 9) | PAINT (MIXTURE ; EXTERIEUR BOIS MAT VELOUTE 9) | (MIXTURE ; EXTERIEUR BOIS MAT VELOUTE 9) | Not regulated | Not regulated |
| Transport document description | | | | |
| UN 1263 PAINT (MIXTURE ; EXTERIEUR BOIS MAT VELOUTE 9), 3, III, (D/E) | UN 1263 PAINT (MIXTURE ; EXTERIEUR BOIS MAT VELOUTE 9), 3, III | UN 1263 (MIXTURE ; EXTERIEUR BOIS MAT VELOUTE 9) | Not regulated | Not regulated |
| 14.3. Transport hazard class(es) | | | | |
| 3 | 3 | Not applicable | Not regulated | Not regulated |

IMPRESSION EXTERIEUR BOIS



Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

| ADR | IMDG | IATA | ADN | RID |
|---|---|-----------------------------------|---------------|---------------|
|  |  | Not applicable | Not regulated | Not regulated |
| 14.4. Packing group | | | | |
| III | III | Not applicable | Not regulated | Not regulated |
| 14.5. Environmental hazards | | | | |
| Dangerous for the environment: No | Dangerous for the environment: No Marine pollutant: No | Dangerous for the environment: No | Not regulated | Not regulated |
| No supplementary information available | | | | |

14.6. Special precautions for user

Overland transport

| | |
|---|--|
| Transport regulations (ADR) | : Not subject to this regulation if Q <450l |
| Classification code (ADR) | : F1 |
| Special provisions (ADR) | : 163, 640E, 650, 367 |
| Limited quantities (ADR) | : 5I |
| Excepted quantities (ADR) | : E1 |
| Packing instructions (ADR) | : P001, IBC03, LP01, R001 |
| Special packing provisions (ADR) | : PP1 |
| Mixed packing provisions (ADR) | : MP19 |
| Portable tank and bulk container instructions (ADR) | : T2 |
| Portable tank and bulk container special provisions (ADR) | : TP1, TP29 |
| Tank code (ADR) | : LGBF |
| Vehicle for tank carriage | : FL |
| Transport category (ADR) | : 3 |
| Special provisions for carriage - Packages (ADR) | : V12 |
| Special provisions for carriage - Operation (ADR) | : S2 |
| Hazard identification number (Kemler No.) | : 30 |
| Orange plates | :   |

| | |
|-------------------------------|--------|
| Tunnel restriction code (ADR) | : D/E |
| EAC code | : •3YE |

Transport by sea

| | |
|------------------------------------|--|
| Transport regulations (IMDG) | : Non soumis à la réglementation IMDG si Q < 30 l |
| Special provisions (IMDG) | : 163, 223, 955, 367 |
| Limited quantities (IMDG) | : 5 L |
| Excepted quantities (IMDG) | : E1 |
| Packing instructions (IMDG) | : P001, LP01 |
| Special packing provisions (IMDG) | : PP1 |
| IBC packing instructions (IMDG) | : IBC03 |
| Tank instructions (IMDG) | : T2 |
| Tank special provisions (IMDG) | : TP1, TP29 |
| EmS-No. (Fire) | : F-E |
| EmS-No. (Spillage) | : S-E |
| Stowage category (IMDG) | : A |
| Properties and observations (IMDG) | : Miscibility with water depends upon the composition. |

Air transport

No data available

IMPRESSION EXTERIEUR BOIS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

| EU restriction list (REACH Annex XVII) | |
|--|--|
| Reference code | Applicable on |
| 3(a) | IMPRESSION EXTERIEUR BOIS ; Hydrocarbons, C9-C11, isoalkanes, cyclics, < 2% aromatics |
| 3(b) | Hydrocarbons, C9-C11, isoalkanes, cyclics, < 2% aromatics ; Isotridecylalcohol, ethoxylated, phosphated, compd. with N,N-dimethylcyclohexanamine ; 2-ethylhexanoic acid, zirconium salt ; 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime ; Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics |
| 3(c) | Isotridecylalcohol, ethoxylated, phosphated, compd. with N,N-dimethylcyclohexanamine |
| 40. | IMPRESSION EXTERIEUR BOIS ; Hydrocarbons, C9-C11, isoalkanes, cyclics, < 2% aromatics |

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : < 300 g/l

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Other information, restrictions and prohibition regulations : VOC Directive 2004/42/EC - Decorative paints and varnishes
Labelling according to Regulation (EC) No. 1272/2008 [CLP]

IMPRESSION EXTERIEUR BOIS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

| Occupational diseases | |
|-----------------------|---|
| Code | Description |
| RG 25 | Diseases resulting from the inhalation of mineral dust containing crystalline silica (quartz, cristobalite, tridymite), crystalline silicates (kaolin, talc), graphite or coal. |
| RG 36 | Diseases caused by oils and fats of mineral or synthetic origin |
| RG 84 | Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide |

Germany

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime is listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

| Indication of changes | | | |
|-----------------------|-----------------------|----------|----------|
| Section | Changed item | Change | Comments |
| | Supersedes version of | Modified | |

| Abbreviations and acronyms: | |
|-----------------------------|---|
| CLP | Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 |
| REACH | Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006 |
| ADN | European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways |
| ADR | European Agreement concerning the International Carriage of Dangerous Goods by Road |
| ATE | Acute Toxicity Estimate |
| BCF | Bioconcentration factor |
| BLV | Biological limit value |
| BOD | Biochemical oxygen demand (BOD) |
| COD | Chemical oxygen demand (COD) |
| DMEL | Derived Minimal Effect level |

IMPRESSION EXTERIEUR BOIS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

| Abbreviations and acronyms: | |
|-----------------------------|--|
| DNEL | Derived-No Effect Level |
| EC-No. | European Community number |
| EC50 | Median effective concentration |
| EN | European Standard |
| IARC | International Agency for Research on Cancer |
| IATA | International Air Transport Association |
| IMDG | International Maritime Dangerous Goods |
| LC50 | Median lethal concentration |
| LD50 | Median lethal dose |
| LOAEL | Lowest Observed Adverse Effect Level |
| NOAEC | No-Observed Adverse Effect Concentration |
| NOAEL | No-Observed Adverse Effect Level |
| NOEC | No-Observed Effect Concentration |
| OECD | Organisation for Economic Co-operation and Development |
| OEL | Occupational Exposure Limit |
| PBT | Persistent Bioaccumulative Toxic |
| PNEC | Predicted No-Effect Concentration |
| RID | Regulations concerning the International Carriage of Dangerous Goods by Rail |
| SDS | Safety Data Sheet |
| STP | Sewage treatment plant |
| ThOD | Theoretical oxygen demand (ThOD) |
| TLM | Median Tolerance Limit |
| VOC | Volatile Organic Compounds |
| CAS-No. | Chemical Abstract Service number |
| N.O.S. | Not Otherwise Specified |
| vPvB | Very Persistent and Very Bioaccumulative |
| ED | Endocrine disrupting properties |

Data sources

: Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Training advice

: Normal use of this product shall imply use in accordance with the instructions on the packaging.

IMPRESSION EXTERIEUR BOIS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

Other information

: The working conditions of the user are not known to us, the information provided in this safety data sheet are based on the State of our knowledge and on both national and Community regulations. The mixture should not be used for other uses as those specified in section 1 without first obtaining prior written handling instructions. It is always the responsibility of the user to take all the necessary measures to meet the requirements of the laws and local regulations. The information provided in this safety data sheet should be considered a description of the safety requirements to this mixture and not as a guarantee of the properties of it.

The working conditions of the user are not known to us, the information provided in this safety data sheet are based on the State of our knowledge and on both national and Community regulations. The mixture should not be used for other uses as those specified in section 1 without first obtaining prior written handling instructions. It is always the responsibility of the user to take all the necessary measures to meet the requirements of the laws and local regulations. The information provided in this safety data sheet should be considered a description of the safety requirements to this mixture and not as a guarantee of the properties of it.

| Full text of H- and EUH-statements: | |
|-------------------------------------|---|
| Acute Tox. 3 (Dermal) | Acute toxicity (dermal), Category 3 |
| Acute Tox. 4 (Inhalation:dust,mist) | Acute toxicity (inhalation:dust,mist) Category 4 |
| Acute Tox. 4 (Inhalation:vapour) | Acute toxicity (inhalation:vapour) Category 4 |
| Acute Tox. 4 (Oral) | Acute toxicity (oral), Category 4 |
| Aquatic Chronic 2 | Hazardous to the aquatic environment – Chronic Hazard, Category 2 |
| Asp. Tox. 1 | Aspiration hazard, Category 1 |
| Carc. 2 | Carcinogenicity, Category 2 |
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
| EUH208 | Contains 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime(96-29-7). May produce an allergic reaction. |
| EUH210 | Safety data sheet available on request. |
| EUH211 | Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. |
| Eye Dam. 1 | Serious eye damage/eye irritation, Category 1 |
| Eye Irrit. 2 | Serious eye damage/eye irritation, Category 2 |
| Flam. Liq. 3 | Flammable liquids, Category 3 |
| H226 | Flammable liquid and vapour. |
| H302 | Harmful if swallowed. |
| H304 | May be fatal if swallowed and enters airways. |
| H311 | Toxic in contact with skin. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |
| H332 | Harmful if inhaled. |
| H336 | May cause drowsiness or dizziness. |
| H351 | Suspected of causing cancer. |

IMPRESSION EXTERIEUR BOIS

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EC) No. 453/2010

| Full text of H- and EUH-statements: | |
|-------------------------------------|--|
| H361d | Suspected of damaging the unborn child. |
| H411 | Toxic to aquatic life with long lasting effects. |
| Repr. 2 | Reproductive toxicity, Category 2 |
| Skin Irrit. 2 | Skin corrosion/irritation, Category 2 |
| Skin Sens. 1 | Skin sensitisation, Category 1 |
| STOT SE 3 | Specific target organ toxicity – Single exposure, Category 3, Narcosis |

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.