

RESSOURCE SATINE SOLVANTE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 31/08/2017 Revision date: 07/10/2021 Supersedes version of: 07/10/2021 Version: 2.5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : SATINE SOLVANTE
Product code : 015ST
Type of product : PAINT
Product group : Trade product

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : For professional use only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

Ressource
Rue de Mousselière
FR- 30133 Les Angles
FRANCE
T +33(0)490254245
contact@ressource-decoration.com - www.ressource-peintures.com

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
France	ORFILA		+33 1 45 42 59 59	This number provides contact details for all French Poison Control centers. These poison and toxicovigilance centers provide free medical assistance (excluding call costs), 24 hours a day, 7 days a week.
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	16/17 Framlington Place Newcastle-upon-Tyne NE2 4AB	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
Carcinogenicity Not classified
Specific target organ toxicity – Single exposure, Category 3, Narcosis H336
Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. May cause drowsiness or dizziness.

SATINE SOLVANTE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS02

GHS07

Signal word (CLP)

: Warning

Contains

: Hydrocarbons, C9-C11, isoalkanes, cyclics, < 2% aromatics ; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hazard statements (CLP)

: H226 - Flammable liquid and vapour.
H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.
P312 - Call a POISON CENTRE or doctor if you feel unwell.

EUH-statements

: EUH210 - Safety data sheet available on request.
EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
EUH066 - Repeated exposure may cause skin dryness or cracking.
EUH208 - Contains 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime(96-29-7). May produce an allergic reaction.

Extra phrases

: For professional users only.

2.3. Other hazards

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9-C11, isoalkanes, cyclics, < 2% aromatics	CAS-No.: 1174522-20-3 EC-No.: 919-857-5 REACH-no: 01-2119463258-33	11,9195 – 18,806	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304
Titanium dioxide	CAS-No.: 13463-67-7 EC-No.: 236-675-5 EC Index-No.: 022-006-002 REACH-no: 01-2119489379-17	10,77518 – 14,6791	Carc. 2, H351
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: 64742-48-9 EC-No.: 919-857-5 REACH-no: 01-2119463258-33	2,503 – 5,006	Flam. Liq. 3, H226 Acute Tox. Not classified (Inhalation:vapour) STOT SE 3, H336 Asp. Tox. 1, H304

SATINE SOLVANTE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Calcium carbonate	CAS-No.: 471-34-1 EC-No.: 207-439-9 REACH-no: 01-2119486795-18	2,2236 – 3,59482	Acute Tox. 4 (Inhalation:dust,mist), H332
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	EC-No.: 918-481-9 REACH-no: 01-2119457273-39	1 – 5	Asp. Tox. 1, H304
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime	CAS-No.: 96-29-7 EC-No.: 202-496-6 EC Index-No.: 616-014-00-0 REACH-no: 01-2119539477-28	0,1 – 1	Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation:vapour), H332 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351
dipropylene glycol methyl ether substance with a Community workplace exposure limit	CAS-No.: 34590-94-8 EC-No.: 252-104-2 REACH-no: 01-2119450011-60	≤ 0,09562	Not classified

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing.
First-aid measures after eye contact	: Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after skin contact	: Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
------------------------------	--------------------------------------------------

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	------------------------------------------------------------------------------------------------------------------------------------------

SATINE SOLVANTE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray.

Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Poland - Occupational Exposure Limits

Local name	Benzyna do lakierów
NDS (OEL TWA)	300 mg/m ³
NDSch (OEL STEL)	900 mg/m ³

SATINE SOLVANTE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
Switzerland - Occupational Exposure Limits	
Local name	Naphta* lourd (pétrole), hydro-traité
MAK (OEL TWA) [1]	300 mg/m ³
MAK (OEL TWA) [2]	50 ppm
KZGW (OEL STEL)	600 mg/m ³
KZGW (OEL STEL) [ppm]	100 ppm
Remark	4x15*
dipropylene glycol methyl ether (34590-94-8)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	(2-Methoxymethylethoxy)-propanol
IOEL TWA	308 mg/m ³
IOEL TWA [ppm]	50 ppm
Remark	Skin
Austria - Occupational Exposure Limits	
Local name	Dipropylenglykolmonomethylether (Isomerengemisch)
MAK (OEL TWA)	307 mg/m ³
MAK (OEL TWA) [ppm]	50 ppm
MAK (OEL STEL)	614 mg/m ³
MAK (OEL STEL) [ppm]	100 ppm
Remark	H
Belgium - Occupational Exposure Limits	
Local name	Dipropylèneglycolmonométhyléther
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
Remark	D
Bulgaria - Occupational Exposure Limits	
Local name	пропанол•
OEL TWA	308 mg/m ³
Croatia - Occupational Exposure Limits	
Local name	(2-Metoksimetiletoksi)– – propanol
GVI (OEL TWA) [1]	308 mg/m ³
GVI (OEL TWA) [2]	50 ppm
Remark	K, EU*
Czech Republic - Occupational Exposure Limits	
Local name	propanol(2-Methoxymethylethoxy)-(technická sm s isomer)
PEL (OEL TWA)	270 mg/m ³
PEL (OEL TWA) [ppm]	44,6 ppm
NPK-P (OEL C)	550 mg/m ³
NPK-P (OEL C) [ppm]	90,8 ppm

SATINE SOLVANTE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

dipropylene glycol methyl ether (34590-94-8)	
Denmark - Occupational Exposure Limits	
Local name	Dipropylenglycolmethylether (1994)
OEL TWA [1]	300 mg/m ³
OEL TWA [2]	50 ppm
Estonia - Occupational Exposure Limits	
Local name	Dipropüleenglükooli monometüüleeter (2-etoksümetüületoksü)-propanool
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
Finland - Occupational Exposure Limits	
Local name	(2-Metoksimetyylietoksi)- propanoli
HTP (OEL TWA) [1]	310 mg/m ³
HTP (OEL TWA) [2]	50 ppm
France - Occupational Exposure Limits	
Local name	(2-méthoxyméthylethoxy)-propanol
VME (OEL TWA)	308 mg/m ³
VME (OEL TWA) [ppm]	50 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	(2-Methoxymethylethoxy)propanol(Isomerengemisch)
AGW (OEL TWA) [1]	310 mg/m ³
AGW (OEL TWA) [2]	50 ppm
Remark	DFG,EU
Greece - Occupational Exposure Limits	
OEL TWA	600 mg/m ³
OEL TWA [ppm]	100 ppm
OEL STEL	900 mg/m ³
OEL STEL [ppm]	150 ppm
Hungary - Occupational Exposure Limits	
Local name	(2-METOXIMETILETOXI)-PROPANOL (Dipropilénglikol-monometil-éter)
AK (OEL TWA)	308 mg/m ³
CK (OEL STEL)	308 mg/m ³
Ireland - Occupational Exposure Limits	
Local name	(2-Methoxymethylethoxy)-l-propanol
OEL TWA [1]	308 mg/m ³
OEL TWA [2]	50 ppm
Italy - Occupational Exposure Limits	
Local name	(2-Metossimetilotossi)-propanolo
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm

SATINE SOLVANTE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

dipropylene glycol methyl ether (34590-94-8)	
Latvia - Occupational Exposure Limits	
Local name	Metoksipropoksi propanols (dipropilēnglikola monometilēteris,DPM)
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
Lithuania - Occupational Exposure Limits	
Local name	2-(2-metoksipropoksi)-propanolis (2-etoksimetiletoksi)-propanolis, dipropilenglikolio monometilēteris
IPRV (OEL TWA)	300 mg/m ³
IPRV (OEL TWA) [ppm]	50 ppm
TPRV (OEL STEL)	450 mg/m ³
TPRV (OEL STEL) [ppm]	75 ppm
Malta - Occupational Exposure Limits	
Local name	(2-Methoxymethylethoxy)-propanol
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
Netherlands - Occupational Exposure Limits	
Local name	Dipropyleenglycolmethylether
TGG-8u (OEL TWA)	300 mg/m ³
Poland - Occupational Exposure Limits	
Local name	(2-Metoksymetyloetoksy)propanol
NDS (OEL TWA)	240 mg/m ³
NDSch (OEL STEL)	480 mg/m ³
Portugal - Occupational Exposure Limits	
Local name	2-Metoximetiletoxiopropanol (DPGME)
OEL TWA [ppm]	100 ppm
OEL STEL [ppm]	150 ppm
Romania - Occupational Exposure Limits	
Local name	(2-metoximetiletoxi)-propanol
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
Slovenia - Occupational Exposure Limits	
Local name	(2-metoksimetiletoksi)propanol (mešanica izomer)
OEL TWA	308 mg/m ³
OEL TWA [ppm]	50 ppm
Spain - Occupational Exposure Limits	
Local name	Éter metílico de dipropilenglicol
VLA-ED (OEL TWA) [1]	308 mg/m ³
VLA-ED (OEL TWA) [2]	50 ppm

SATINE SOLVANTE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

dipropylene glycol methyl ether (34590-94-8)	
Remark	Vía dérmica: (Indica que, en las exposiciones a esta sustancia, la aportación por la vía cutánea puede resultar significativa para el contenido corporal total si no se adoptan medidas para prevenir la absorción. En estas situaciones, es aconsejable la utilización del control biológico para poder cuantificar la cantidad global absorbida del contaminante. Para más información véase el Apartado 5 de este documento.), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país.)
Sweden - Occupational Exposure Limits	
Local name	Dipropylene glycol monomethyl ether
NGV (OEL TWA)	300 mg/m ³
NGV (OEL TWA) [ppm]	50 ppm
KTV (OEL STEL)	450 mg/m ³
KTV (OEL STEL) [ppm]	75 ppm
United Kingdom - Occupational Exposure Limits	
Local name	(2-methoxymethylethoxy) propanol
WEL TWA (OEL TWA) [1]	308 mg/m ³
WEL TWA (OEL TWA) [2]	50 ppm
Remark	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity)
Norway - Occupational Exposure Limits	
Local name	(2-Metoksymetyletoksy)-propanol
Grønseverdi (OEL TWA) [1]	300 mg/m ³
Grønseverdi (OEL TWA) [2]	50 ppm
Switzerland - Occupational Exposure Limits	
Local name	Oxyde de dipropylèneglycolméthyle (mélange d'isomères)
MAK (OEL TWA) [1]	300 mg/m ³
MAK (OEL TWA) [2]	50 ppm
KZGW (OEL STEL)	300 mg/m ³
KZGW (OEL STEL) [ppm]	50 ppm
Remark	15 min
Calcium carbonate (471-34-1)	
France - Occupational Exposure Limits	
Local name	Calcium (carbonate de)
VME (OEL TWA)	10 mg/m ³
Latvia - Occupational Exposure Limits	
Local name	Kalcijakarbonāts
OEL TWA	6 mg/m ³
Poland - Occupational Exposure Limits	
Local name	Węglan wapnia pyły 10)

SATINE SOLVANTE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Calcium carbonate (471-34-1)	
NDS (OEL TWA)	10 mg/m ³
Portugal - Occupational Exposure Limits	
Local name	Carbonato de cálcio
OEL TWA	10 mg/m ³
Titanium dioxide (13463-67-7)	
Austria - Occupational Exposure Limits	
Local name	Titandioxid (Alveolarstaub)
MAK (OEL TWA)	5 mg/m ³
MAK (OEL STEL)	10 mg/m ³
Belgium - Occupational Exposure Limits	
Local name	Titane (dioxyde de)
OEL TWA	10 mg/m ³
Bulgaria - Occupational Exposure Limits	
Local name	Титанов диоксид, респирабилен прах
OEL TWA	10 mg/m ³
Croatia - Occupational Exposure Limits	
Local name	Titanov dioksid
GVI (OEL TWA) [1]	10 mg/m ³ inhalable dust 4 mg/m ³ respirable dust
Denmark - Occupational Exposure Limits	
Local name	Titandioxid, beregnet som Ti
OEL TWA [1]	6 mg/m ³
Estonia - Occupational Exposure Limits	
Local name	Titaanoksiid
OEL TWA	5 mg/m ³
France - Occupational Exposure Limits	
Local name	Titane (dioxyde de), en Ti
VME (OEL TWA)	10 mg/m ³
Greece - Occupational Exposure Limits	
OEL TWA	10 mg/m ³
Latvia - Occupational Exposure Limits	
Local name	Titānadioksīds
OEL TWA	10 mg/m ³
Lithuania - Occupational Exposure Limits	
Local name	Titano dioksidas
IPRV (OEL TWA)	5 mg/m ³
Portugal - Occupational Exposure Limits	
Local name	Dióxido de titânio
OEL TWA	10 mg/m ³

SATINE SOLVANTE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Titanium dioxide (13463-67-7)	
Spain - Occupational Exposure Limits	
Local name	Dióxido de titanio
VLA-ED (OEL TWA) [1]	10 mg/m ³
Sweden - Occupational Exposure Limits	
Local name	Titanium dioxide total dust
NGV (OEL TWA) [ppm]	5 ppm
United Kingdom - Occupational Exposure Limits	
Local name	Titanium dioxide
WEL TWA (OEL TWA) [1]	4 mg/m ³ respirable 10 mg/m ³ total inhalable
Iceland - Occupational Exposure Limits	
Local name	Títandíoxíð, sem Ti
OEL TWA	6 mg/m ³
Norway - Occupational Exposure Limits	
Local name	Titandioksid
Grenseverdi (OEL TWA) [1]	5 mg/m ³
Switzerland - Occupational Exposure Limits	
Local name	Dioxyde de titane
MAK (OEL TWA) [1]	3 mg/m ³
USA - ACGIH - Occupational Exposure Limits	
Local name	Titanium dioxide
ACGIH OEL TWA	1 mg/m ³
Remark (ACGIH)	LRT irr; A3

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



SATINE SOLVANTE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: white.
Odour	: Organic solvents.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Flammable liquid and vapour.
Explosive limits	: Not available
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: 48 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: > 7
Viscosity, kinematic	: Not available
Viscosity, dynamic	: 500 – 2000 cP
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: 1,418 g/cm ³
Relative density	: 1,418
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : < 300 g/l

SATINE SOLVANTE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Hydrocarbons, C9-C11, isoalkanes, cyclics, < 2% aromatics (1174522-20-3)	
LD50 oral rat	> 5000 mg/kg (OECD 401 method)
LD50 dermal rat	> 5000 mg/kg (OECD 402 method)
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (96-29-7)	
LD50 oral rat	≈ 900 mg/kg
LD50 dermal rat	≈ 1000 mg/kg
LC50 Inhalation - Rat	≈ 13,2 mg/l
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
LD50 oral rat	> 6000 mg/kg
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 5000 mg/kg
LC50 Inhalation - Rat	> 5610 mg/m ³
LC50 Inhalation - Rat (Vapours)	> 5 mg/l/4h
Calcium carbonate (471-34-1)	
LD50 oral rat	6450 mg/kg
LD50 dermal rat	> 2000 mg/kg (OECD 402)
LC50 Inhalation - Rat	> 3 mg/l/4h

SATINE SOLVANTE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Titanium dioxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 6,82 mg/l/4h
Skin corrosion/irritation	: Not classified pH: > 7
Serious eye damage/irritation	: Not classified pH: > 7
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified.
Reproductive toxicity	: Not classified
STOT-single exposure	: May cause drowsiness or dizziness.
Hydrocarbons, C9-C11, isoalkanes, cyclics, < 2% aromatics (1174522-20-3)	
STOT-single exposure	May cause drowsiness or dizziness.
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
Viscosity, kinematic	1,25 mm ² /s

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not classified
Hazardous to the aquatic environment, long-term (chronic)	: Not classified

Hydrocarbons, C9-C11, isoalkanes, cyclics, < 2% aromatics (1174522-20-3)	
LC50 - Fish [1]	> 1000 mg/l 96 Hours (Onchorhynchus mykiss) (OECD 203 method)
EC50 - Crustacea [1]	> 1000 mg/l 48 Hours (Daphnia magma) (OECD 202 method)
ErC50 algae	> 1000 mg/l 72 Hours (Scenedesmus subspicatus) (OECD 201 method)
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime (96-29-7)	
LC50 - Fish [1]	> 100 mg/l 96 Hours (Oryzias latipes)
EC50 - Crustacea [1]	201 mg/l 48 Hours (Daphnia magma)
ErC50 algae	11,8 mg/l 72 Hours
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-48-9)	
LC50 - Fish [1]	> 1000 mg/l 96 heures (Oncorhynchus mykiss)
EC50 - Crustacea [1]	> 1000 mg/l 48 heures (Daphnies)
EC50 72h - Algae [1]	> 1000 mg/l

SATINE SOLVANTE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Titanium dioxide (13463-67-7)

LC50 - Fish [1]	> 1000 mg/l 96 Hours (Fundulus heteroclitus)
EC50 - Crustacea [1]	> 1000 mg/l 48 Hours (Daphnia magna)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available



SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapours may accumulate in the container.

SECTION 14: Transport information

In accordance with ADR / IMDG

ADR	IMDG
14.1. UN number or ID number	
UN 1263	UN 1263
14.2. UN proper shipping name	
PAINT	PAINT
Transport document description	
UN 1263 PAINT, 3, III, (D/E)	UN 1263 PAINT, 3, III
14.3. Transport hazard class(es)	
3	3
	
14.4. Packing group	
III	III

SATINE SOLVANTE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878


ADR	IMDG
14.5. Environmental hazards	
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No
No supplementary information available	

14.6. Special precautions for user

Special transport precautions : Avoid release to the environment.

Overland transport

Transport regulations (ADR) : Not subject to this regulation if Q <450l
Classification code (ADR) : F1
Special provisions (ADR) : 163, 640E, 650, 367
Limited quantities (ADR) : 5l
Excepted quantities (ADR) : E1
Packing instructions (ADR) : P001, IBC03, LP01, R001
Special packing provisions (ADR) : PP1
Mixed packing provisions (ADR) : MP19
Portable tank and bulk container instructions (ADR) : T2
Portable tank and bulk container special provisions (ADR) : TP1, TP29
Tank code (ADR) : LGBF
Vehicle for tank carriage : FL
Transport category (ADR) : 3
Special provisions for carriage - Packages (ADR) : V12
Special provisions for carriage - Operation (ADR) : S2
Hazard identification number (Kemler No.) : 30
Orange plates :



Tunnel restriction code (ADR) : D/E

Transport by sea

Transport regulations (IMDG) : Non soumis à la réglementation IMDG si Q < 30 l
Special provisions (IMDG) : 163, 223, 955, 367
Limited quantities (IMDG) : 5 L
Excepted quantities (IMDG) : E1
Packing instructions (IMDG) : P001, LP01
Special packing provisions (IMDG) : PP1
IBC packing instructions (IMDG) : IBC03
Tank instructions (IMDG) : T2
Tank special provisions (IMDG) : TP1, TP29
EmS-No. (Fire) : F-E
EmS-No. (Spillage) : S-E
Stowage category (IMDG) : A
Properties and observations (IMDG) : Miscibility with water depends upon the composition.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SATINE SOLVANTE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)	
Reference code	Applicable on
3(a)	SATINE SOLVANTE ; Hydrocarbons, C9-C11, isoalkanes, cyclics, < 2% aromatics ; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
3(b)	SATINE SOLVANTE ; Hydrocarbons, C9-C11, isoalkanes, cyclics, < 2% aromatics ; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics ; 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime ; Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
40.	SATINE SOLVANTE ; Hydrocarbons, C9-C11, isoalkanes, cyclics, < 2% aromatics ; Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : < 300 g/l

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

France

Other information, restrictions and prohibition regulations : Classification according to directives 67/548/EEC and 1999/45/EC
VOC Directive 2004/42/EC - Decorative paints and varnishes
Labelling of building products or products used for wall or floor coatings and paints and varnishes concerning their emissions of volatile pollutants (Order of 19 April 2011)
Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).

SATINE SOLVANTE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazardous Incident Ordinance (12. BImSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

SZW-lijst van kankerverwekkende stoffen : 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime is listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Class for fire hazard : Class II-1
Store unit : 5 liter
Classification remarks : R10 <H226;H336>; Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product
The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
	Supersedes version of	Modified	

Abbreviations and acronyms:

CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration

SATINE SOLVANTE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
N.O.S.	Not Otherwise Specified
vPvB	Very Persistent and Very Bioaccumulative
ED	Endocrine disrupting properties

- Data sources : Classification according to Classification, Labelling and Packaging of Substances and Mixtures (SEA) Regulation published in the Official Journal numbered 28848 on December 11, 2013. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.
- Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.
- Other information : The working conditions of the user are not known to us, the information provided in this safety data sheet are based on the State of our knowledge and on both national and Community regulations. The mixture should not be used for other uses as those specified in section 1 without first obtaining prior written handling instructions. It is always the responsibility of the user to take all the necessary measures to meet the requirements of the laws and local regulations. The information provided in this safety data sheet should be considered a description of the safety requirements to this mixture and not as a guarantee of the properties of it.
- The working conditions of the user are not known to us, the information provided in this safety data sheet are based on the State of our knowledge and on both national and Community regulations. The mixture should not be used for other uses as those specified in section 1 without first obtaining prior written handling instructions. It is always the responsibility of the user to take all the necessary measures to meet the requirements of the laws and local regulations. The information provided in this safety data sheet should be considered a description of the safety requirements to this mixture and not as a guarantee of the properties of it.

Full text of H- and EUH-statements:	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3

SATINE SOLVANTE

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:	
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Acute Tox. Not classified (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Not classified
Asp. Tox. 1	Aspiration hazard, Category 1
Carc. 2	Carcinogenicity, Category 2
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH208	Contains 2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime(96-29-7). May produce an allergic reaction.
EUH210	Safety data sheet available on request.
EUH211	Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.
Skin Sens. 1	Skin sensitisation, Category 1
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.