

EXTERIOR WALL

Highly resistant, unsaponifiable facade paint.



RECOMMENDED USE

Outdoors.

On vertical surfaces.

Substrates: All types of masonry: mortar plaster, cement, levelled concrete, fiber cement, plaster in good condition.

BENEFITS

- Highly microporous.
- Highly resistant to bad weather.
- Excellent adhesion even on difficult substrates.
- Can be directly applied onto the substrate without using a primer.

SURFACE PREPARATION

The surface must be perfectly cleaned, dusted and dry.

Old non-adherent paint: Strip the surface bare.

Powdery surfaces: Use a pressure washer or simply brush and dust.

Application tools: Apply using with a brush or a pile façade roller.

APPLICATION

Apply two coats of Exterior Wall using a brush or roller, diluting it with 5% White Spirit.

We recommend testing the dilution on a small area to determine the right percentage (the paint should not be too thin and it should glide easily over the surface).

The best dilution should be easy to apply and result in a beautiful finish.

GENERAL INFORMATION

Finish: Matte.

Coverage: 9-10m²/L per coat depending on the porosity of the substrate.

Drying time: 2h (dry to the touch).

Second coat: Approx. 24h (depending on temperature and air humidity).

Solid content: 73% in weight, 48% in volume.

Density: 1.6g/cm³.

How to clean your equipment: White Spirit.

Packaging: 0.5L, 2.5L, 5L and 10L.

Storage: 1 year in its original unopened packaging.

Tinting: Available in white and in 2 bases.

HANDLE WITH CARE

Use in temperatures between +5°C and +30°C. Do not use when relative humidity is more than 75%. Do not apply in rainy weather, nor on frozen or overheated surfaces. Shades whose solar absorption coefficient exceeds 0.7 (strong colours) are not recommended and cannot be guaranteed.

REGULATORY INFORMATION

AFNOR Classification: Family I - Class 7b1.
AFNOR P84-403: Class D2.
AFNOR EN1062-1 - Class E3V2W1A0.

VOC⁽¹⁾: The 2010 EU limit value for this product (cat A/c) is 430g/L.
This product contains maximum 410g/L VOC.

Safety: Refer to the Safety Data Sheet (SDS). Complies with current legislation.

⁽¹⁾ *Volatile Organic Compounds: Directive 2004/42/EC.*

* *Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions).*