

TENSION-FREE CEILING MATTE

Special ceiling paint based on limed oil.



RECOMMENDED USE

Indoors.

On ceilings. In all indoor spaces.

Substrates: All standard building materials that have been properly primed.

BENEFITS

- Bright white, highly opaque and filling paint.
- Class 2² wet abrasion resistance (after 28 days of drying): low maintenance.
- Little surface preparation. Does not damage or remove any previous adhesive layers of paint or whitewash.
- Can be covered while wet which will allow to reintegrate the premises sooner.
- Protects against soot, nicotine and water damage stains. Allows surfaces to breathe.

SURFACE PREPARATION

The surface must be perfectly cleaned, dusted and dry.

Powdery, gelatinous, whitewashed, limewashed or adherent non-greasy stained surfaces: Degrease appropriately if necessary.

Powdery or very powdery surfaces: Apply our Solvent-Based Primer diluted with 5-10% White Spirit or our Universal Primer.

New surfaces: Apply our Undercoat for Light or Dark Colors, or Undercoat for Regular Work or all-purpose primer.

Application tools: Apply using a brush, a 10mm microfibre roller or an airless sprayer.

APPLICATION

Ready to use. Do not dilute. Apply generously in 1 or 2 coats depending on the condition of the surface, using a brush or a 10mm microfibre roller. The 2nd coat can be applied while wet except if surface is stained, in which case it is necessary to wait 24 hours for the surface to dry.

GENERAL INFORMATION

Finish: Matte.

Gloss: 2 to 3GU at 60°.

Coverage: 11-13m²/L per coat depending on your choice of equipment and dilution.

Drying time: 3-4h (dry to the touch).

Second coat: Approx. 24h on stained surfaces or while still wet (depending on temperature and air humidity).

Solid content: 70% in weight (+/- 2%), 40% in volume (+/- 2%).

Density: 1.61g/cm³.

How to clean your equipment: White Spirit.

Packaging: 2.5L, 5L and 12L.

Storage: 1 year in its original unopened packaging. Keep away from frost.

HANDLE WITH CARE

Use in temperatures between +5°C and +30°C. Do not use when relative humidity is more than 75%.

REGULATORY INFORMATION

AFNOR Classification: Family I - Class 2b/4a.

VOC⁽¹⁾: The 2010 EU limit value for this product (cat A/i) is 500g/L.
This product contains maximum 375g/L VOC.

Safety: Refer to the safety Data Sheet (SDS). Complies with current legislation.

⁽¹⁾ Volatile Organic Compounds: Directive 2004/42/EC.

⁽²⁾ According to ISO 11998 and EN 13300, the paint film is resistant to cleaning with a sponge, using gentle household products. Take care as washing may leave a sheen on some strong colours.

* Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions).

TDS No. 946 Edition 7 April 2016. This Technical Data Sheet cancels and replaces the previous editions for the same product. As techniques evolve constantly, it is the sole responsibility of our customers to check with our services - before use - that this Technical Data Sheet is the most recent edition.

Document available on our website www.ressource-peintures.com