

## CEILING MATTE

Matte insulating alkyd-based emulsion for ceilings.

---

### RECOMMENDED USE

#### Indoors.

On ceilings. In all indoor rooms.

Substrates: All standard building materials that have been properly primed.

### BENEFITS

- Matte insulating alkyd-based emulsion for ceilings.
- Highly covering and sealing.
- Bright white.
- Does not leave streaks, marks or lines.
- Wet abrasion resistance.
- Class 2<sup>(2)</sup> (after 28 days of drying).
- Microporous. Little surface preparation needed.
- Protects against stains (nicotine, soot).

### SURFACE PREPARATION

The surface must be perfectly cleaned, dusted and dry. Apply the appropriate primer and/or undercoat for the substrate.

**Powdery, gelatinous, whitewashed or limewashed surfaces:** No need to wash the surface if it is adherent and not greasy. If not, degrease appropriately and apply our Universal Primer.

**Plasterboard, plaster derivatives and other porous surfaces:** Apply our Universal Primer.

**Old paint in good condition (not very porous surfaces):** Sand and dust. Wash and rinse if necessary. Apply our Undercoat Light or Dark Colors, or our Undercoat for Regular Work.

**Application tools:** Apply using a special acrylic brush, a 1/2" (12mm) non-drip roller, an airless or pneumatic sprayer.

### APPLICATION

Once the undercoat is completely dry, apply two coats of Ceiling Matte using a brush or roller. The second coat can be applied after 4 hours of drying, except if the surface being painted is stained in any way in which case, allow 24 hours for drying. Dilute with 5% water.

With an airless or traditional paint sprayer and depending on the type of equipment used, the paint may need to be diluted with 10 to 20% water. The dilution will depend on the porosity of the surface. We recommend testing the dilution on a small area to determine the right percentage (the paint should not be too thin and it should glide easily over the surface).

### GENERAL INFORMATION

**Appearance:** Deep Matte.

**Gloss:** 2 at 60° and 85°.

**Coverage:** 410sq.Ft/Gal; 1080sq.Ft/10L (10m<sup>2</sup>/L approx.) per coat depending on your choice of equipment and dilution.

**Drying time:** 3-4h (dry to the touch).

## GENERAL INFORMATION

**Second coat:** 4-5h. On stained surfaces: 24h (depending on the temperature and air humidity).

**Solid content:** 66% in weight (+/-2%), 47% in volume (+/-2%).

**Density:** 1.58g/cm<sup>3</sup> (+/-0.05%) in white.

**How to clean your equipment:** Water.

**Packaging:** 1Gal and 10L.

**Storage:** 1 year in its original unopened packaging. Keep away from frost.

## HANDLE WITH CARE

Use in temperatures between 46°F (8°C) and 95°F (35°C). Do not use when relative humidity reaches more than 70%.

## REGULATORY INFORMATION

**VOC regulatory**<sup>(1)</sup>: This product contains 80g/L VOC in use.

**Safety:** Refer to the safety Data Sheet (SDS) for health and safety information.

<sup>(1)</sup> Volatile Organic Compounds: Federal Regulations 40CFR59.

<sup>(2)</sup> According to ISO 11998 and EN 13300, the paint film is resistant to cleaning with a sponge, using gentle household products. Take care as washing may leave a sheen on some strong colors.