


FLOOR PAINT

Multipurpose floor paint (wood, concrete, tiles).

Matte  — Gloss

Care : washable finish

Recommended use : rooms with light traffic only

Easy to apply 



RECOMMENDED USE

Indoors.

Horizontal surfaces and vertical tiles. In all rooms, including stairs and garages. The hardness of the film also allows to paint furniture.

Substrates: Parquet (bare or already painted hardwood floors, laminate floors), concrete floors (bare or already painted), tiles.

BENEFITS

- Polyurethane dispersion-based finishing paint with excellent scratch resistance.
- The silanized acrylic binder reinforces its adhesion to all types of surfaces.
- Light satin finish.
- Suitable for light to medium traffic, in all rooms.
- Washable, resistant to mild chemicals.
- Class 1⁽²⁾ wet abrasion resistance (after 28 days of drying): low maintenance.

SURFACE PREPARATION

The surface must be perfectly dusted, dry and very clean. Apply 2 coats of Floor Paint onto the surface (diluting with up to 3% water) and preparing the surface as follows:

Bare wood: Scrape off all resinous residues. Sand the surface until smooth. Vacuum to remove all dust and wipe with a damp cloth. Allow the wood to dry. Moisture content should be less than 10%. Treat knotty or resinous areas with our Solvent-Based Primer to block any tannins. Next, apply the Undercoat for Light or Dark Colors. Finish with two coats of Floor Paint in the colour of your choice, respecting the recommended drying time.

Previously painted wood: Remove all flaking and loose paint. Sand the surface until smooth. Vacuum to remove all dust and wipe with a damp cloth. Allow the wood to dry. Moisture content should be less than 10%. Next, apply the Undercoat for Light or Dark Colors. Finish with two coats of Floor Paint in the colour of your choice, respecting the recommended drying time.

Varnished wood: Sand to roughen the surface. Vacuum to remove all dust and wipe with a damp cloth. Leave to dry. Then apply a coat of Superprimer. When painting bright colours, apply our tinted Undercoat for Dark Colors. Finish with two coats of Floor Paint in the shade of your choice, respecting the recommended drying time. Do not use for waxed wood.

New concrete floors: Allow the screed to dry for at least 3 months before painting new concrete. Remove all traces of laitance and dust the surface. Apply one coat of Superprimer to enable the finish to adhere to the concrete floor. When painting bright colours, apply our tinted Undercoat for Dark Colors. Finish with two coats of Floor Paint in the shade of your choice, respecting the recommended drying time.

Painted concrete floors: Remove all flaking and loose paint. Old or damaged surfaces must be repaired and filled. If using a levelling compound, allow to dry for at least 1 week. Sand and roughen the surface. Vacuum to remove any dust and apply the Superprimer first to the areas where the concrete is bare. Leave to dry and then apply a coat of Superprimer over the entire surface. When painting bright colours, apply our tinted Undercoat for Dark Colors. Finish with two coats of Floor Paint in the shade of your choice, respecting the recommended drying time.

Tiled floors: Degrease the tiles and the joints using detergent, (the Floor Paint will not adhere without proper degreasing). If the sealing is damaged in places, scrape off the non-adherent parts and seal again. For shiny tiles, sand to roughen the surface. Clean and dry. Apply one coat of Superprimer. When painting bright colours, apply our tinted Undercoat for Dark Colors. Finish with two coats of Floor Paint in the shade of your choice, respecting the recommended drying time.

SURFACE PREPARATION

Application tools: Apply using a special acrylic brush, a 10mm roller, a traditional paint sprayer or an airless sprayer intended for horizontal painting.

GENERAL INFORMATION

Appearance: Light Satin.

Gloss: 18 to 20GU at 60° and 30 to 40GU at 85°.

Coverage: 10-12m²/L per coat depending on your choice of equipment and dilution.

Drying time: 1h (dry to the touch).

Second coat: 4-5h depending on the temperature and air humidity.

Solid content: 48% in weight, 34% in volume.

Density: 1.27g/cm³.

How to clean your equipment: Water.

Packaging: 1L, 2.5L and 5L.

Storage: 1 year in its original unopened packaging. Keep away from frost.

Tinting: All Ressource colours (available in 5 bases).

HANDLE WITH CARE

Use in temperatures between +10°C and +30°C. Do not use when relative humidity reaches more than 80%.

Wait 24 to 48 hours before walking and placing objects (furniture or vehicles) on the surface. Wait 14 to 18 days before moving objects on the surface. The Floor Paint will reach maximum hardness after 18 days.

REGULATORY INFORMATION

AFNOR Classification: Family I - Class 6a/7b2.

VOC⁽¹⁾: The 2010 EU limit value for this product [cat A/i] is 140g/L. This product contains maximum 60g/L VOC.

Safety: Refer to the safety Data Sheet (SDS). Complies with current legislation.

⁽¹⁾ Volatile Organic Compounds: Directive 2004/42/EC.

⁽²⁾ According to ISO 11998 and EN 13300, the paint film is resistant to cleaning with a sponge, using gentle household products. Take care as washing may leave a sheen on some strong colours.

* Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions).