

## ROUGH PRIMER

Facilitates the application of decorative coatings.



### RECOMMENDED USE

#### Indoors.

For vertical surfaces, in all rooms.

Substrates: On all standard building materials that have been properly primed.

### BENEFITS

Our Rough Primer is opaque and regulates absorption. Specially designed to facilitate the application of thick coatings using a trowel.

### SURFACE PREPARATION

The surface must be perfectly cleaned, dusted and dry. Do not apply on powdery or porous substrates.

**Plasterboard, old painted surfaces (slightly porous or non-porous):** Gently sand and dust. Wash and rinse, if necessary.

**Porous or powdery surfaces:** Cover with our Universal Primer.

**Application tools:** Apply using a 12mm microstar non-drip roller or a brush. Do not use an airless or pneumatic sprayer due to the grains of silica.

### APPLICATION

Apply one coat of Rough Primer with a brush or roller, diluting it with approx. 5% water.

We recommend testing the dilution on a small area to determine the right percentage (the paint should not be too thin and it should glide easily over the surface).

### GENERAL INFORMATION

**Appearance:** Matte.

**Coverage:** Approx. 6-8m<sup>2</sup>/L depending on the porosity of the surface.

**Drying time:** 4-5h dry to the touch.

**Second coat:** Approx. 12h depending on the temperature and air humidity.

**Solid content:** 67% in weight (+/- 2%), 53% in volume (+/- 2%).

**Density:** 1.45g/cm<sup>3</sup> (+/- 0.05).

**How to clean your equipment:** Water.

**Packaging:** 1L, 2.5L and 10L.

**Storage:** 1 year in its original unopened packaging. Keep away from frost.

### HANDLE WITH CARE

Use in temperatures between +8°C and + 35°C. Do not use when relative humidity reaches more than 70%.

## REGULATORY INFORMATION

**AFNOR Classification:** Family I - Class 7b2/7a2.

**VOC<sup>(1)</sup>:** The 2010 EU limit value for this product (cat A/g) is 30g/L.  
This product contains maximum 29g/L VOC.

**Safety:** Refer to the Safety Data Sheet (SDS). Complies with current legislation.

<sup>(1)</sup> *Volatile Organic Compounds: Directive 2004/42/EC.*

*\* Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions).*

*TDS No. 910 Edition 11 April 2024. This Technical Data Sheet cancels and replaces the previous editions for the same product. As techniques evolve constantly, it is the sole responsibility of our customers to check with our services - before use - that this Technical Data Sheet is the most recent edition.*

Document available on our website [www.ressource-peintures.com](http://www.ressource-peintures.com)