

MATTE PROTECTIVE VARNISH

Matte protective varnish for light-coloured matte interior paints.



RECOMMENDED USE

Indoors.

For vertical surfaces. In all rooms.

Substrates: All surfaces decorated with Ressource matte paint made with bases 8 and 9.

BENEFITS

Highly transparent, decorative and protecting acrylic resin-based varnish. Intended for the protection of light-coloured matte interior paints. Improves the washable properties of the finish. Can be washed frequently. Resistant to detergent and cleaning agents. Very hard protective film.

SURFACE PREPARATION

All surfaces must be perfectly cleaned, dusted and dry.

All dry and clean surfaces (Ressource matte paint made with bases number 8 and 9): Before application, check the substrate contains no water-soluble tannins or nicotine.

Application tools: Apply using a 5mm lacquer roller, a brush, an airless or a traditional paint sprayer.

APPLICATION

Using a brush or a roller, apply one or two coats of Matte Protective Varnish diluted with approx. 5% water.

With an airless or traditional paint sprayer and depending on the type of equipment used, the paint may need to be diluted with 5 to 10% water. Test the dilution on a piece of cardboard or an inconspicuous area to obtain the best dilution.

We recommend testing the dilution on a small area to determine the right percentage (the paint should not be too thin and it should glide easily over the surface).

GENERAL INFORMATION

Finish: Matte.

Coverage: 15m²/L per coat depending on the porosity of the surface.

Drying time: 30mins (dry to the touch).

Second coat: Approx. 2h (depending on the temperature and air humidity).

Solid content: 43% in weight, 40% in volume.

Density: 1.06g/cm³.

How to clean your equipment: Water.

Packaging: 0.5L and 1L.

Storage: 1 year in its original unopened packaging. Keep away from frost.

HANDLE WITH CARE

Use in temperatures between +5°C and +30°C. Do not use when relative humidity reaches more than 75%. Check the substrate doesn't contain any water-soluble tannins or nicotine. During the application process, frequently examine in grazing light that the entire surface has been varnished. Avoid any build up and lumps which may lead to white patches.

REGULATORY INFORMATION

AFNOR Classification: Family I - Class 7b2.

VOC⁽¹⁾: The 2010 EU limit value for this product (cat A/e) is 130g/L. This product contains maximum 50g/L VOC.

Safety: Refer to the Safety Data Sheet (SDS). Complies with current legislation.

⁽¹⁾ *Volatile Organic Compounds: Directive 2004/42/EC.*

** Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions).*

TDS No. 913 Edition 11 April 2024. This Technical Data Sheet cancels and replaces the previous editions for the same product. As techniques evolve constantly, it is the sole responsibility of our customers to check with our services - before use - that this Technical Data Sheet is the most recent edition.

Document available on our website www.ressource-peintures.com