

RUSTPROOF PRIMER

Corrosion protection for ferrous metals.

RECOMMENDED USE

Outdoors.
In all climates and atmospheres.
Substrates: All metallic surfaces.

BENEFITS

Corrosion protection.

SURFACE PREPARATION

On all dry, degreased and descaled metallic surfaces and after careful brushing.
Application tools: Apply a brush, 10mm roller or a traditional paint sprayer.

APPLICATION

Apply one coat of undiluted Rustproof Primer with a brush or a 10mm roller.
When using a paint sprayer, dilute using 10% synthetic thinner.
Metallic surfaces: Degrease and descale if necessary. Brush carefully.

GENERAL INFORMATION

Appearance: Satin.
Coverage: 10-12m²/L per coat depending on the porosity of the surface.
Drying time: 4h (dry to the touch).
Second coat: Approx. 24h depending on temperature and air humidity.
Solid content: 80% in weight, 60% in volume.
Density: 1.50g/cm³.
How to clean your equipment: White Spirit.
Packaging: 0.5L and 1L.
Storage: 1 year in its original unopened packaging.

HANDLE WITH CARE

Use in temperatures between +5°C and +30°C. Do not use when relative humidity reaches more than 75%.
Never paint in atmospheric conditions that may cause condensation or on frozen or overheated surfaces, or in conditions that would cause the paint to dry abnormally quickly. (Wind, sun, rain etc.).

REGULATORY INFORMATION

AFNOR Classification: Family I - Class 4a/10h.

VOC⁽¹⁾: The 2010 EU limit value for this product (cat A/i) is 500g/L.
This product contains maximum 300g/L VOC.

Safety: Refer to the Safety Data Sheet (SDS). Complies with current legislation.

⁽¹⁾ *Volatile Organic Compounds: Directive 2004/42/EC.*

** Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions).*

TDS No. 916 Edition 11 April 2024. This Technical Data Sheet cancels and replaces the previous editions for the same product. As techniques evolve constantly, it is the sole responsibility of our customers to check with our services - before use - that this Technical Data Sheet is the most recent edition.

Document available on our website www.ressource-peintures.com