



VELVET SATIN

Washable Velvet Satin Acrylic Copolymer Paint.

Matte  Gloss
Care : washable finish
Recommended use: all rooms including humid rooms
Easy to apply 



RECOMMENDED USE

Indoors.

Can be used on interior woodwork, in all rooms.

Substrates: All primed wood and wood-based substrates. If you are painting iron, apply a rustproof primer first.

BENEFITS

Dilutable acrylic copolymer paint with a beautifully soft and smooth satin finish. Low gloss leachable finish Class 1⁽²⁾ wet abrasion resistance (after 28 days of drying): easy to maintain. Non-yellowing and no residual stickiness.

SURFACE PREPARATION

The surface must be perfectly clean, dusted and dry. For low opacity shades, we recommend you use Undercoat for Dark Colors in the same shade as the top coat (see list of colours in store).

Painted surfaces: Wash, rinse and leave to dry completely. On satin or glossy paints, sand lightly to roughen the surface and remove any dust. Apply Undercoat for Light or Dark Colors.

Low-porosity surfaces: Sand and dust gently. Apply a coat of Undercoat for Regular Work or Undercoat for Light or Dark Colors.

Very porous or powdery surfaces: Sand and dust gently. Apply a coat of Universal Primer.

Tannic wood: Apply a coat of Solvent-Based Primer.

Application tools: Apply with a brush for acrylic paint, a 10mm microfibre roller or an airless or conventional sprayer. For a smooth finish, use a 10mm microfibre roller and smooth over using a spalter.

APPLICATION

Once the undercoat has dried completely, dilute with approximately 5% water and apply two coats of Satin Velvet, using a brush or a roller.

With an airless or a conventional sprayer, the paint may need to be diluted with 10 to 20% water. Make several tests on a piece of cardboard or an inconspicuous area to find the best dilution which should be both easy to apply and give a nice, tight finish.

GENERAL INFORMATION

Appearance: Satin Velvet.

Gloss: 8 to 10GU at 60°.

Coverage: 13-16m²/L per coat depending on dilution and application method.

Drying time: 30mins (dry to the touch).

Second coat: Approx. 4h depending on on temperature and air humidity.

Solid content: 56% in weight, 41% in volume.

Density: 1.45g/cm³.

How to clean your equipment: Water.

GENERAL INFORMATION

Packaging: 0.5L, 1L, 2.5L, 5L and 10L.

Storage: 1 year in its original unopened packaging. Keep away from frost.

Tinting: All Ressource colours (available in 5 bases).

HANDLE WITH CARE

Apply between +8°C and +35°C. Do not apply when relative humidity exceeds 70%.

For low opacity shades, it is strongly recommended to use a Undercoat for Dark Colors in the same shade as the finish (see list of available colours in store).

REGULATORY INFORMATION

AFNOR Classification: Family I - Class 7b2.

VOC⁽¹⁾: The 2010 EU limit value for this product (cat A/d) is 130g/L.

This product contains maximum 60g/L VOC.

Safety: Refer to the Safety Data Sheet (SDS). Complies with current legislation.

⁽¹⁾ Volatile Organic Compounds: Directive 2004/42/EC.

⁽²⁾ According to ISO 11998 and EN 13300, the paint film is resistant to cleaning with a sponge, using gentle household products. Take care as washing may leave a sheen on some strong colours.

* Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions).