

WATER-BASED WAX

Colorless protective wax in aqueous phase.

RECOMMENDED USE

Indoors.

For vertical surfaces, in all rooms.

Substrates: Burnished or Smoothed Lime, Roman Plaster.

BENEFITS

- Beautiful waxed finish.
- Protects lime-based coatings.
- Can easily be covered when redecorating.

SURFACE PREPARATION

The surface must be perfectly cleaned, dusted and dry. Allow at least 24h for the lime plaster to dry completely.

Dry and clean mineral plaster coatings: The substrate must be completely dry.

Application tools: Apply either with a stainless steel trowel or with a new 3/8" (10mm) microfibre roller and a stainless steel trowel.

APPLICATION

Ready to use. Do not dilute.

After the surface you wish to protect has dried off completely, apply a coat of Water-based Wax using a stainless steel trowel, taking care to work in small areas with gentle and rounded movements. The wax can also be applied with a new 3/8" (10mm) microfibre roller. Apply the product with the roller randomly in 4.6sq.in (30cm²) areas and smooth the wax with stainless steel trowel as evenly as possible.

Work in complete wall sections, do not make linear stops.

Allow to dry for approximately 24 hours (under normal temperature and humidity conditions).

The Water-based Wax does not sheen after drying.

Caution: applying this Wax will slightly darken the original color. Wait until the wax has dried completely to appreciate the final result.

GENERAL INFORMATION

Appearance: Waxed.

Coverage: 710sq.Ft/Gal and 188sq.Ft/L (17m²/L approx.) depending on the porosity of the surface.

Drying time: Approx. 24h.

Solid content: 35% in weight, 34% in volume.

Density: 1,01g/cm³.

How to clean your equipment: Water.

Packaging: 1L.

Storage: 1 year in its original unopened packaging. Keep away from frost.

HANDLE WITH CARE

Use in temperatures between +41°F (5°C) and +86°C (30°C). Do not use when relative humidity reaches more than 75%.

**REGULATORY
INFORMATION**

VOC regulatory⁽¹⁾: This product contains 130g/L VOC in use.

Safety: Refer to the safety Data Sheet (SDS) for health and safety information.

⁽¹⁾ *Volatile Organic Compounds: Federal Regulations 40CFR59.*

TDS No. 930 Edition 14 April 2024. This Technical Data Sheet cancels and replaces the previous editions for the same product. As techniques evolve constantly, it is the sole responsibility of our customers to check with our services - before use - that this Technical Data Sheet is the most recent edition.

Document available on our website www.ressource-peintures.com