

WATER-BASED WAX

Colourless protective wax in aqueous phase.



RECOMMENDED USE

Indoors.

For vertical surfaces, in all rooms.

Substrates: Burnished or Smoothed Lime, Roman Plaster.

BENEFITS

- Beautiful waxed finish.
- Protects lime-based coatings.
- Can easily be covered when redecorating.

SURFACE PREPARATION

The surface must be perfectly cleaned, dusted and dry. Allow at least 24h for the Lime plaster to dry completely.

Dry and clean mineral plaster coatings: The substrate must be completely dry.

Application tools: Apply either with a stainless steel trowel or with a new 10mm microfibre roller and a stainless steel trowel.

APPLICATION

Ready to use. Do not dilute.

After the surface you wish to protect has dried off completely, apply a coat of Water-based Wax using a stainless steel trowel, taking care to work in small areas with gentle and rounded movements. The wax can also be applied with a new 10mm microfibre roller. Apply the product with the roller randomly in 30cm² areas and smooth the wax with stainless steel trowel as evenly as possible.

Work in complete wall sections, do not make linear stops.

Allow to dry for approximately 24 hours (under normal temperature and humidity conditions).

The Water-based Wax does not sheen after drying.

Caution: applying this Wax will slightly darken the original colour. Wait until the wax has dried completely to appreciate the final result.

GENERAL INFORMATION

Appearance: Waxed.

Coverage: 15-20m²/L depending on the porosity of the surface.

Drying time: Approx. 24h.

Solid content: 35% in weight, 34% in volume.

Density: 1,01g/cm³.

How to clean your equipment: Water.

Packaging: 1L and 2.5L.

Storage: 1 year in its original unopened packaging. Keep away from frost.

HANDLE WITH CARE

Use in temperatures between +5°C and + 30°C. Do not use when relative humidity reaches more than 75%.

**REGULATORY
INFORMATION**

AFNOR Classification: Family I - Class 7b2.

VOC⁽¹⁾: The 2010 EU limit value for this product (cat A/I) is 200g/L.
This product contains maximum 15g/L VOC.

Safety: Refer to the safety Data Sheet (SDS). Complies with current legislation.

⁽¹⁾ *Volatile Organic Compounds: Directive 2004/42/EC*

Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions).

TDS No. 930 Edition 11 April 2024. This Technical Data Sheet cancels and replaces the previous editions for the same product. As techniques evolve constantly, it is the sole responsibility of our customers to check with our services - before use - that this Technical Data Sheet is the most recent edition.

Document available on our website www.ressource-peintures.com