

## SUPERPRIMER

Multipurpose bond primer.

---

### RECOMMENDED USE

#### Indoors.

For horizontal and vertical surfaces. For all indoor rooms.

Substrates: All standard building materials and especially on glass, earthenware, non-ferrous metals, common building plastics, door frames, factory-painted cladding, concrete floors and tiling.

### BENEFITS

Enables to decorate difficult surfaces. Can be coated with both water-based and solvent-based finishes.

### SURFACE PREPARATION

All surfaces must be perfectly cleaned, dusted and dry. Clean the surface using the appropriate mechanical tools or chemicals.

**Glossy or satin surfaces:** Sand to remove the polish and dust.

**Non-ferrous surfaces:** Degrease and remove any traces of oxidation.

**Factory-painted plastic, glass and earthenware:** Degrease using a solvent-based product and sand to remove the polish and dust.

**Application tools:** Apply using either a brush, a 3/8" (10mm) microfibre roller, an airless or a traditional paint sprayer.

### APPLICATION

Apply one coat of Superprimer diluted with approx. 5% water. For best results, the first finishing coat should be applied the next day. This way, the interfacial adherence will be optimal.

Caution: the final hardening process may take longer in cold and wet weather. We recommend checking that the Superprimer has properly bonded to the substrate before applying the finish (lightly scrape a small area with your nail. The Superprimer must be hard under the nail and must adhere well to the substrate).

If the product is not covered after 48 hours of drying, sand lightly to roughen the surface to improve the adhesion.

### GENERAL INFORMATION

**Finish:** Satin.

**Coverage:** 450sq.Ft/Gal; 58sq.Ft/Half Liter (11m<sup>2</sup>/L approx.) per coat on the porosity of the surface.

**Drying time:** 1h (dry to the touch).

**Second coat:** 12-24h (depending on the temperature and air humidity).

**Solid content:** 37% in weight, 33% in volume.

**Density:** 1.08g/cm<sup>3</sup>.

**How to clean your equipment:** Water.

**Packaging:** 0.5L and 1Gal.

**Storage:** 1 year in its original unopened packaging. Keep away from frost.

**HANDLE WITH CARE**

Use in temperatures between 46°F (8°C) and 95°F (35°C). Do not use when relative humidity reaches more than 70%. Do not tint the Superprimer.

**REGULATORY INFORMATION**

**VOC regulatory**<sup>(1)</sup>: This product contains 50g/L VOC in use.

**Safety**: Refer to the safety Data Sheet (SDS) for health and safety information.

<sup>(1)</sup> Volatile Organic Compounds: Federal Regulations 40CFR59.

*TDS No. 933 Edition 14 April 2024. This Technical Data Sheet cancels and replaces the previous editions for the same product. As techniques evolve constantly, it is the sole responsibility of our customers to check with our services - before use - that this Technical Data Sheet is the most recent edition.*

Document available on our website [www.ressource-peintures.com](http://www.ressource-peintures.com)