

UNDERCOAT FOR REGULAR WORK

Porosity homogenizing and absorption regulating undercoat.



RECOMMENDED USE

Indoors.

For vertical surfaces and ceilings. For all indoor rooms.

Substrates: On all standard building materials. Previously painted surfaces in good condition, plasterboard. Not suitable for highly porous or powdery surfaces.

BENEFITS

Undercoat for renovation work on old paintwork. Particularly easy to use. Enhanced with an antirust agent: does not rust nail heads. Homogenises the porosity of the surface and regulates its absorption. Unsaponifiable, microporous and non-yellowing.

SURFACE PREPARATION

The surface must be perfectly cleaned, dusted and dry.

Previously painted surfaces in good condition: Wash and rinse. If the paint is glossy or satin, sand and dust beforehand, then apply the Undercoat for Regular Work.

Cardboard coated Plasterboard, old painted surfaces (slightly porous or non-porous): Dust, then apply the Undercoat for Regular Work.

Application tools: Apply using a brush, 10mm microfibre roller or an airless or traditional paint sprayer.

APPLICATION

Apply one coat of Undercoat for Regular Work with a brush or roller, diluting it with approx. 5% water.

We recommend testing the dilution on a small area to determine the right percentage (the paint should not be too thin and it should glide easily over the surface).

With an airless or traditional paint sprayer and depending on the type of equipment used, the paint may need to be diluted with 10 to 20% water. Test the dilution on a piece of cardboard or an inconspicuous area to obtain the best dilution.

GENERAL INFORMATION

Finish: Matte.

Coverage: 9-11m²/L per coat on the porosity of the surface.

Drying time: 30mins (dry to the touch).

Second coat: 4-5h (depending on the temperature and air humidity).

Solid content: 61% in weight, 44% in volume.

Density: 1.45g/cm³.

How to clean your equipment: Water.

Packaging: 2.5L and 10L.

Storage: 1 year in its original unopened packaging. Keep away from frost.

HANDLE WITH CARE

Use in temperatures between +5°C and +30°C. Do not use when relative humidity reaches more than 75%.

**REGULATORY
INFORMATION**

AFNOR Classification: Family I - Class 7b2.

VOC⁽¹⁾: The 2010 EU limit value for this product (cat A/g) is 30g/L.
This product contains maximum 5g/L VOC.

Safety: Refer to the safety Data Sheet (SDS). Complies with current legislation.

⁽¹⁾ *Volatile Organic Compounds: Directive 2004/42/EC*

Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions).

TDS No. 935 Edition 11 April 2024. This Technical Data Sheet cancels and replaces the previous editions for the same product. As techniques evolve constantly, it is the sole responsibility of our customers to check with our services - before use - that this Technical Data Sheet is the most recent edition.

Document available on our website www.ressource-peintures.com