

WOODEN FLOOR AND PAINT VARNISH

High quality sheer protection for floors and paint.



RECOMMENDED USE

Indoors.

For horizontal and vertical surfaces. For all indoor rooms.

Substrates: Hardwood floors and painted wood floors.

BENEFITS

High-quality protective varnish that doesn't alter the wood's natural colour. Transparent with a slight satin finish, this protection can be used on our Powder Matte finish, in our entire colour range, without altering the shade. High filling power and resistant to dents, scratches and stains. This varnish provides long-lasting protection for all types of natural and painted parquet floors.

SURFACE PREPARATION

The surface must be perfectly dusted, dry and clean. Check before applying the varnish, that there is no nicotine or water-soluble tannins on the surface.

New parquet : Sand using fine sandpaper (120) and dust.

Varnished parquet: Sand the wood bare (60 sandpaper and then 120).

Old waxed parquet: Remove wax and sand (120 sandpaper).

Previously painted surfaces: Sand the wood bare and dust.

Application tools: Apply using a 5mm, 10mm microfibre roller or using a brush for small areas and edges.

APPLICATION

Apply 2 coats of Wooden Floor and Paint Varnish with a brush or a roller diluting with 5% water.

With an airless or traditional paint sprayer and depending on the type of equipment used, the paint may need to be diluted with 10 to 20% water. Test the dilution on a piece of cardboard or an inconspicuous area to obtain the best dilution.

Apply in crossed layers facing the light. Finish varnishing following the wood fibers. For optimal protection, three coats are required. Allow to dry for 4 hours between each coat. We recommend to sand and dust between each coat.

If you wish to paint the substrate before applying sealing it: apply our Universal Primer on the bare substrate, then apply 2 top coats in the desired shade. Leave to dry for 24 hours. Apply 2 coats of Wooden Floor and Paint Varnish. Wait until the varnish is completely dry (48h) to assess the final result. The varnish will ensure best protection 21 days after application. Reintegration of the premises: 10-12h in normal conditions (light traffic).

We recommend testing the dilution on a small area to determine the right percentage (the paint should not be too thin and it should glide easily over the surface).

The right dilution is easy to apply and results in a clean, smooth and beautiful finish.

GENERAL INFORMATION

Finish: Satin.

Gloss: 30GU at 60°.

GENERAL INFORMATION

Coverage: 12-15 m²/L per coat depending on the porosity of the substrate.

Drying time: 1h (dry to the touch).

Second coat: Approx. 4h (depending on the temperature and air humidity).

Solid content: 30% in weight, 28% in volume.

Density: 1.03g/cm³.

How to clean your equipment: Water.

Packaging: 0.5L, 1L and 2.5L.

Storage: 1 year in its original unopened packaging. Keep away from frost.

HANDLE WITH CARE

Use in temperatures between +5°C and +30°C. Do not use when relative humidity reaches more than 75%.

REGULATORY INFORMATION

AFNOR Classification: Family I - Class 6a.

VOC⁽¹⁾: The 2010 EU limit value for this product (cat A/i) is 140g/L. This product contains maximum 99g/L VOC.

Safety: Refer to the safety Data Sheet (SDS). Complies with current legislation.

⁽¹⁾ *Volatile Organic Compounds: Directive 2004/42/EC*

** Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions).*

TDS No. 943 Edition 11 April 2024. This Technical Data Sheet cancels and replaces the previous editions for the same product. As techniques evolve constantly, it is the sole responsibility of our customers to check with our services - before use - that this Technical Data Sheet is the most recent edition.

Document available on our website www.ressource-peintures.com