

## TENSION-FREE CEILING MATTE

Special ceiling paint based on limed oil.



### RECOMMENDED USE

#### Indoors.

On ceilings. In all indoor spaces.

Substrates: All standard building materials that have been properly primed.

### BENEFITS

- Bright white, highly opaque and filling paint.
- Class 2<sup>(2)</sup> wet abrasion resistance (after 28 days of drying): low maintenance.
- Little surface preparation. Does not damage or remove any previous adhesive layers of paint or whitewash.
- Can be covered while wet which will allow to reintegrate the premises sooner.
- Protects against soot, nicotine and water damage stains. Allows surfaces to breathe.

### SURFACE PREPARATION

The surface must be perfectly cleaned, dusted and dry.

**Powdery, gelatinous, whitewashed, limewashed or adherent non-greasy stained surfaces:** Degrease appropriately if necessary.

**Powdery or very powdery surfaces:** Apply our Solvent-Based Primer diluted with 5-10% White Spirit or our Universal Primer.

**New surfaces:** Apply our Undercoat for Light or Dark Colors, or Undercoat for Regular Work or all-purpose primer.

**Application tools:** Apply using a brush, a 10mm microfibre roller or an airless sprayer.

### APPLICATION

Ready to use. Do not dilute. Apply generously in 1 or 2 coats depending on the condition of the surface, using a brush or a 10mm microfibre roller. The 2<sup>nd</sup> coat can be applied while wet except if surface is stained, in which case it is necessary to wait 24 hours for the surface to dry.

### GENERAL INFORMATION

**Finish:** Matte.

**Gloss:** < 2GU at 60° and 85°.

**Coverage:** 11-13m<sup>2</sup>/L per coat depending on your choice of equipment and dilution.

**Drying time:** 3-4h (dry to the touch).

**Second coat:** Approx. 24h on stained surfaces or while still wet (depending on temperature and air humidity).

**Solid content:** 70% in weight (+/- 2%), 40% in volume (+/- 2%).

**Density:** 1.61g/cm<sup>3</sup>.

**How to clean your equipment:** White Spirit.

**Packaging:** 2.5L, 5L and 12L.

**Storage:** 1 year in its original unopened packaging. Keep away from frost.

## HANDLE WITH CARE

Use in temperatures between +5°C and +30°C. Do not use when relative humidity is more than 75%.

## REGULATORY INFORMATION

**AFNOR Classification:** Family I - Class 2b/4a.

**VOC<sup>(1)</sup>:** The 2010 EU limit value for this product (cat A/i) is 500g/L.  
This product contains maximum 375g/L VOC.

**Safety:** Refer to the safety Data Sheet (SDS). Complies with current legislation.

<sup>(1)</sup> Volatile Organic Compounds: Directive 2004/42/EC.

<sup>(2)</sup> According to ISO 11998 and EN 13300, the paint film is resistant to cleaning with a sponge, using gentle household products. Take care as washing may leave a sheen on some strong colours.

\* Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions).