

## SOLVENT-BASED PRIMER

Solvent-based filling and fixing primer.



### RECOMMENDED USE

#### Indoors.

For vertical surfaces and ceilings, in all rooms.

Substrates: Old suitably washed paintwork, plaster, plasterboard, water-based coatings, other coatings, interior woodwork.

### BENEFITS

- Matte finish, high filling and opaque primer. Facilitates adhesion of all kinds of paint on all surfaces.
- Consolidates powdery surfaces and homogenises the porosity of porous surfaces.
- Isolates and blocks wood stains and tannins.
- Increases the lifetime open time of your finish.

### SURFACE PREPARATION

New surfaces must be perfectly cleaned, dusted and dry. When using on our lime paints, allow the lime to dry for at least 48 hours before covering it with the Solvent-based Primer.

**Porous or powdery surfaces:** Sand and dust, apply the Solvent-based Primer diluted with 5 to 10% White Spirit.

**Non-porous and old painted surfaces:** Wash and once completely dry, apply the Solvent-based Primer diluted with 3 to 5% White Spirit.

**Wood and wood derivatives:** Sand and dust off, apply the Solvent-based Primer, diluted with 5 to 10% White Spirit.

**Alkaline substrates, old concrete, lime-based coatings:** Ensure the surface is completely dry (48 hours minimum) and that there are no traces of humidity or laitance (treat with an acid solution if necessary). Apply the Solvent-based Primer, diluted with 10% White Spirit.

**Application tools:** Apply using either a brush, a 12mm non-drip roller or 10mm microstar roller.

### APPLICATION

Apply the solvent-based primer with a brush or roller, diluting with approx. 5-10% White Spirit.

When painting over old paint, apply a Solvent-based Primer using a brush or roller, diluting it with approximately 3-5% White Spirit.

With an airless or traditional paint sprayer and depending on the type of equipment used, the paint may need to be diluted with 10 to 20% White Spirit.

Test the dilution on a piece of cardboard or an inconspicuous area to obtain the best dilution.

We recommend testing the dilution on a small area to determine the right percentage (the paint should not be too thin and it should glide easily over the surface).

### GENERAL INFORMATION

**Appearance:** Matte.

**Gloss:** 2 to 3GU at 60°.

**Coverage:** 10-15m<sup>2</sup>/L depending on the porosity of the surface.

## GENERAL INFORMATION

**Drying time:** 4h.

**Second coat:** Approx. 12h hardening will take longer if the weather is cold and damp.

**Solid content:** 82% in weight, 61% in volume.

**Density:** 1.68g/cm<sup>3</sup>.

**How to clean your equipment:** White Spirit.

**Packaging:** 1L, 2.5L and 12L.

**Storage:** 1 year in its original unopened packaging. Keep away from frost.

## HANDLE WITH CARE

Use in temperatures between +5°C and + 30°C. Do not use when relative humidity reaches more than 75%.

## REGULATORY INFORMATION

**AFNOR Classification:** Family I - Class 4a.

**VOC<sup>(1)</sup>:** The 2010 EU limit value for this product (cat A/h) is 750g/L.

This product contains maximum 400g/L VOC.

**Safety:** Refer to the safety Data Sheet (SDS). Complies with current legislation.

<sup>(1)</sup> Volatile Organic Compounds: Directive 2004/42/EC.

\* Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions).