



ELEGANT MATTE

Smooth acrylic-vinyl paint.

Matte  — Gloss

Care : wipeable finish

Recommended use : all rooms preferably dry rooms

Easy to apply 

RECOMMENDED USE

Indoors.

On vertical surfaces. In all indoor spaces preferably dry rooms.

Substrates: All standard building materials that have been properly primed. If you are painting iron, apply a rustproof primer first.

BENEFITS

- Smooth and opaque acrylic paint.
- Very low VOC content.
- Pleasant to the touch.
- Beautiful finish.
- Class 2⁽²⁾ wet abrasion resistance (after 28 days drying).
- Quick to dry.

SURFACE PREPARATION

The surface must be perfectly cleaned, dusted and dry. Apply the appropriate primer and/or undercoat for the substrate. For low opacity shades, use the Undercoat Dark Colors in the color of the finish (refer to the list of available shades in store).

Plasterboard, old paint in good condition (not very porous surfaces): Sand and dust, wash and once completely dry, apply a Undercoat for Regular Work or a Undercoat Light or Dark Colors.

Brick stone, plaster... (porous, powdery or chalky surfaces): Apply our Universal Primer followed by a tinted undercoat if necessary.

Application tools: Apply using a special acrylic brush, a 3/8" (10mm) microfibre roller, an airless or pneumatic sprayer. For a smooth finish, use a 3/8" (10mm) microfibre roller and smooth evenly with a spalter brush.

APPLICATION

Once the undercoat is completely dry, apply two coats of Elegant Matte using a brush or roller, diluting with 5% water.

We recommend testing the dilution on a small area to determine the right percentage (the paint should not be too thin and it should glide easily over the surface).

With an airless or traditional paint sprayer and depending on the type of equipment used, the paint may need to be diluted with 10 to 20% water. Test the dilution on a piece of cardboard or an inconspicuous area to obtain the best dilution and a beautiful finish.

GENERAL INFORMATION

Appearance: Velvet Matte.

Gloss: 2 to 3GU at 60° and 8 to 10GU at 85°.

Coverage: 610sq.Ft/Gal; 161sq.Ft/L (15m²/L approx.) per coat depending on your choice of equipment and dilution.

Drying time: 30mins (dry to the touch).

Second coat: 4-5h depending on the temperature and air humidity.

GENERAL INFORMATION

Solid content: 61% in weight (+/-2%), 44% in volume (+/-2%).

Density: 1.57g/cm³ (+/-0.05%) in white.

How to clean your equipment: Water.

Packaging: 1L, 1Gal and 10L.

Storage: 1 year in its original unopened packaging. Keep away from frost.

Tinting: All Ressource colors (available in 5 bases).

HANDLE WITH CARE

Use in temperatures between 46°F (8°C) and 95°F (35°C). Do not use when relative humidity reaches more than 70%. For low opacity shades, it is strongly recommended to use the Undercoat for Dark Colors in the same color as the finish (see list of available shades in store).

REGULATORY INFORMATION

VOC regulatory⁽¹⁾: This product contains 50g/L VOC in use.

Safety: Refer to the safety Data Sheet (SDS) for health and safety information.

⁽¹⁾ Volatile Organic Compounds: Federal Regulations 40CFR59.

⁽²⁾ According to ISO 11998 and EN 13300, the paint film is resistant to cleaning with a sponge, using gentle household products. Take care as washing may leave a sheen on some strong colors.