

YVES KLEIN® VELVET MATTE

Resistant velvet matte wall paint.

RECOMMENDED USE

Indoors.

On walls and vertical surfaces. In indoor spaces with moderate passage (corridors and living rooms).

Substrates: All standard building materials that have been properly primed.

BENEFITS

- Acrylic based paint.
- Highly opaque, great filling power and very smooth (odorless, quick to dry, no lingering tack or stickiness).

SURFACE PREPARATION

The surface must be perfectly cleaned, dusted and dry.

Only use the Yves Klein® Undercoat.

Plasterboard, old paint in good condition (not very porous surfaces): Sand and dust. Wash and rinse if necessary. Apply the Yves Klein® Undercoat .

Brick stone, plaster... (porous, powdery or chalky surfaces): Apply our Universal Primer followed by the Yves Klein® Undercoat.

Application tools: Apply using a special acrylic brush, a 3/8" (10mm) microstar roller, an airless sprayer.

APPLICATION

Once the Yves Klein® Undercoat is completely dry, apply two coats of Yves Klein® Velvet Matte using a brush or roller, diluting with 1-2% water at the most.

With an airless or traditional paint sprayer and depending on the type of equipment used, the paint may need to be diluted with 10 to 15% water. Test the dilution on a piece of cardboard or an inconspicuous area to obtain the best dilution.

We recommend testing the dilution on a small area to determine the right percentage (the paint should not be too thin and it should glide easily over the surface). The right dilution is easy to apply and results in a clean, smooth and beautiful finish.

GENERAL INFORMATION

Finish: Velvet Matte.

Gloss: 0 to 1GU at 60° and 15 to 25GU at 85°.

Coverage: 610sq.Ft/Gal and 160sq.Ft/L (15m²/L approx.) per coat.

Drying time: 2h (dry to the touch).

Second coat: Approx. 4-6h (depending on the temperature and air humidity).

Solid content: 58% (+/-2%) in weight, 44% (+/-2%) in volume.

Density: 1.32g/cm³ (+/-0.05%).

How to clean your equipment: Water.

**GENERAL
INFORMATION**

Packaging: 1L.

Storage: 1 year in its original unopened packaging. Keep away from frost and high temperatures.

HANDLE WITH CARE

Use in temperatures between 46°F (8°C) and 86°F (30°C). Do not use when relative humidity reaches more than 70%. Slight nuances may appear in the Yves Klein® shade, which are specific to the pigments used, bringing both luminosity and vibration.

**REGULATORY
INFORMATION**

VOC regulatory⁽¹⁾: This product contains 70g/L VOC in use.

Safety: Refer to the safety Data Sheet (SDS) for health and safety information.

⁽¹⁾ *Volatile Organic Compounds: Federal Regulations 40CFR59.*

TDS No. 970 Edition 12 April 2024. This Technical Data Sheet cancels and replaces the previous editions for the same product. As techniques evolve constantly, it is the sole responsibility of our customers to check with our services - before use - that this Technical Data Sheet is the most recent edition.

Document available on our website www.ressource-peintures.com