

YVES KLEIN® VELVET MATTE

Resistant velvet matte wall paint.



RECOMMENDED USE

Indoors.

On walls and vertical surfaces. In indoor spaces with moderate passage (corridors and living rooms).

Substrates: All standard building materials that have been properly primed.

BENEFITS

Acrylic based paint. Highly opaque, great filling power and very smooth (odourless, quick to dry, no lingering tack or stickiness).

SURFACE PREPARATION

The surface must be perfectly cleaned, dusted and dry.

Only use the Yves Klein® Undercoat.

Plasterboard, old paint in good condition (not very porous surfaces): Sand and dust. Wash and rinse if necessary. Apply the Yves Klein® Undercoat .

Brick stone, plaster... (porous, powdery or chalky surfaces): Apply our Universal Primer followed by the Yves Klein® Undercoat.

Application tools: Apply using a special acrylic brush, a 10mm microstar roller, an airless sprayer.

APPLICATION

Once the Yves Klein® Undercoat is completely dry, apply two coats of Yves Klein® Velvet Matte using a brush or roller, diluting with 1-2% water at the most.

With an airless or traditional paint sprayer and depending on the type of equipment used, the paint may need to be diluted with 10 to 15% water. Test the dilution on a piece of cardboard or an inconspicuous area to obtain the best dilution.

We recommend testing the dilution on a small area to determine the right percentage (the paint should not be too thin and it should glide easily over the surface). The right dilution is easy to apply and results in a clean, smooth and beautiful finish.

GENERAL INFORMATION

Finish: Velvet Matte.

Gloss: 0 to 1GU at 60° and 15 to 25GU at 85°.

Coverage: 14-16m²/L per coat.

Drying time: 2h (dry to the touch).

Second coat: Approx. 4-6h (depending on the temperature and air humidity).

Solid content: 58% (+/-2%) in weight, 44% (+/-2%) in volume.

Density: 1.32g/cm³ (+/-0.05%).

How to clean your equipment: Water.

**GENERAL
INFORMATION**

Packaging: 1L and 2.5L.

Storage: 1 year in its original unopened packaging. Keep away from frost and high temperatures.

HANDLE WITH CARE

Use in temperatures between +8°C and +30°C. Do not use when relative humidity reaches more than 70%. Slight nuances may appear in the Yves Klein® shade, which are specific to the pigments used, bringing both luminosity and vibration.

**REGULATORY
INFORMATION**

AFNOR Classification: Family I - Class 7b2.

VOC⁽¹⁾: The 2010 EU limit value for this product (cat A/a) is 30g/L.
This product contains maximum 22g/L VOC.

Safety: Refer to the safety Data Sheet (SDS). Complies with current legislation.

⁽¹⁾ Volatile Organic Compounds: Directive 2004/42/EC.

* Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions).