



RECYCLED PAINT - MATTE FINISH

Velvety matte acrylic paint.

Matte  Gloss
Care : wipeable finish
Recommended use : all rooms preferably dry rooms
Easy to apply 



RECOMMENDED USE

Indoors.

On vertical surfaces. In all indoor spaces preferably dry rooms.

Substrates: On all standard building materials that are properly primed.
On ferrous metals, a coat of Rustproof Primer must be applied beforehand.

BENEFITS

- Taut, opacifying acrylic paint.
- Beautiful velvety matte finish.
- Class 2(?) wet abrasion resistance (achieved after 28 days drying).
- Fast drying.
- Eco-designed: product made with 50% recycled Ressource paint.

SURFACE PREPARATION

All surfaces must be perfectly cleaned, dusted and dry
Apply a primer and/or undercoat suitable for the surface.

Plasterboard, old paint in good condition (low porosity surfaces): Sand lightly and dust thoroughly. Wash and rinse if necessary. Prime with the Recycled Undercoat.

Brick stone, plaster (porous, powdery or chalky surfaces): Dust thoroughly and prime with Universal Primer.

Application tools: Apply using a special acrylic brush, a 10mm microfiber roller.

APPLICATION

After the undercoat has dried completely, apply two coats of Recycled Paint Matte Finish with a brush or roller, diluting with 5% water.

Tip: We recommend testing the dilution rate on a small area to determine the right percentage (the paint should not pull, it should slide easily over the surface to be covered).

Using the airless or traditional spray gun, and depending on the equipment used, the paint may need to be diluted with 10 to 20% water. Test several times on a piece of cardboard or an inconspicuous area until the optimum dilution is reached. The optimum dilution of the paint allows a neat application (good adhesion) and comfortable application.

GENERAL INFORMATION

Appearance: Velvet Matte.

Gloss: 2 to 3GU at 60° and 8 to 10GU at 85°.

Coverage: 14-16m²/L per coat depending on your choice of equipment and dilution.

Drying time: 30mins (dry to the touch).

Second coat: 4-5h depending on the temperature and air humidity.

Solid content: 61% in weight (+/-2%), 44% in volume (+/-2%).

GENERAL INFORMATION

Density: 1.50g/cm³ (+/-0.05%) in white.

How to clean your equipment: Water.

Packaging: 2.5L.

Storage: 1 year in its original unopened packaging. Keep away from frost.

Tinting: 6 colours available and white.

HANDLE WITH CARE

Apply between +5 °C and +30 °C. Please do not apply at relative humidity above 70%.

REGULATORY INFORMATION

AFNOR Classification: Family I - Class 7b2.

VOC⁽¹⁾: The 2010 EU limit value for this product (cat A/a) is 30g/L. This product contains maximum 30g/L VOC.

Safety: Refer to the safety Data Sheet (SDS). Complies with current legislation.

⁽¹⁾ Volatile Organic Compounds: Directive 2004/42/EC.

⁽²⁾ According to ISO 11998 and EN 13300, the paint film is resistant to cleaning with a sponge, using gentle household products. Take care as washing may leave a sheen on some strong colours.

* Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions).