

## RECYCLED UNDERCOAT

Homogenises and regulates the porosity of the base.



### RECOMMENDED USE

#### Indoors.

On vertical surfaces and ceilings. In all indoor rooms.

Substrates: On all usual building materials. Old, well-adhering paint, plasterboard.  
Not suitable for very porous or powdery bases.

### BENEFITS

- Good opacity.
- Homogenises the porosity of bases and regulates their absorption.
- Promotes adhesion of the finish and gives a neat and durable end result.
- Very good resistance to alkalinity, microporous, does not yellow. Fast drying. Good adhesion on old sanded paint.
- Eco-designed: product made with 50% recycled Ressource paint.

### SURFACE PREPARATION

Materials must be perfectly dust-free, cleaned and dry. In the case of very porous, powdery or flaky bases, use our Universal Primer penetrating and fixing.

**Old paint in good condition (well-adhering paint):** Wash and rinse. If glossy or satin, sand and dust thoroughly before priming with Recycled Undercoat.

**Plasterboard with cardboard skin:** Dust off perfectly and then prime with the Recycled Undercoat.

**Application tools:** Apply with a brush, a 10mm microfiber roller, an airless or traditional sprayer.

### APPLICATION

Apply one coat of Recycled Undercoat with a brush or roller, diluted with 5% water.

With an airless or traditional sprayer, and depending on the type of equipment used, the paint may need to be diluted with 10 to 20% water. Test several times on a piece of cardboard or an inconspicuous area until the optimum dilution is reached.

Tip: We recommend testing the dilution on a small area to determine the right percentage (the paint should not be too thin and it should slide easily over the surface to be covered).

### GENERAL INFORMATION

**Finish:** Matte.

**Coverage:** 9-11m<sup>2</sup>/L depending on the porosity of the surface.

**Drying time:** 30mins (dry to the touch).

**Second coat:** Approx. 4-5h (depending on the temperature and air humidity).

**Solid content:** 58% (+/-2%) in weight, 44% (+/-2%) in volume.

**Density:** 1.41g/cm<sup>3</sup> (+/-0.05).

**How to clean your equipment:** Water.

**GENERAL  
INFORMATION**

**Packaging:** 2.5L.

**Storage:** 1 year in its original unopened packaging. Keep away from frost.

**HANDLE WITH CARE**

Use in temperatures between +5°C and +30°C. Do not use when relative humidity reaches more than 70%.

**REGULATORY  
INFORMATION**

**AFNOR Classification:** Family I - Class 7b2.

**VOC<sup>(1)</sup>:** The 2010 EU limit value for this product (cat A/g) is 30g/L.  
This product contains maximum 30g/L VOC.

**Safety:** Refer to the Safety Data Sheet (SDS). Complies with current legislation.

<sup>(1)</sup> *Volatile Organic Compounds: Directive 2004/42/EC.*

*\* Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions).*

*TDS No. 976 Edition 07 September 2022. This Technical Data Sheet cancels and replaces the previous editions for the same product. As techniques evolve constantly, it is the sole responsibility of our customers to check with our services - before use - that this Technical Data Sheet is the most recent edition.*

Document available on our website [www.ressource-peintures.com](http://www.ressource-peintures.com)