

EXTRA MATTE – LES COULEURS® LE CORBUSIER®

With its deep matte finish, Extra Matte Les Couleurs® Le Corbusier® reveals the full richness and subtlety of the collection's colors. Its powdery, enveloping appearance gently absorbs light, enhances volumes, and gives spaces a natural yet elegant presence. This finish provides a uniform, deeply matte appearance with no lap marks.

For all colors in the Les Couleurs® Le Corbusier® collection, prior application of Undercoat Les Couleurs® Le Corbusier® tinted is essential to reveal the full depth and accuracy of the color.

Gloss: 2 GU⁽¹⁾ (60°/85°).

Cleaning*: wipeable finish.

Recommended use: dry rooms with low to medium traffic.

⁽¹⁾Gloss unit.

*The deep matte finish may be prone to burnishing. Clean gently.



RECOMMENDED USE

Interior.

For walls and ceilings in dry rooms with low to medium traffic. Particularly suitable for bedrooms, offices, living rooms, and dining rooms.

Substrates: all standard, properly prepared and primed building surfaces.
On ferrous substrates, first apply a suitable anti-corrosion primer.

BENEFITS

- Deep matte finish with a powdery, enveloping appearance.
- High filling power.
- Class 2 wet abrasion resistance (after 28 days of drying).
- Wipeable finish; clean gently.
- Formulated to limit the appearance of rust spots around nail and screw heads.
- Accurate reproduction of color depth.

SURFACE PREPARATION

Substrates must be in good condition, dust-free, dry, smooth, and clean.
Apply a suitable primer and/or undercoat for the substrate.

Old adherent paints (non-porous substrates): wash and rinse. Apply Undercoat Les Couleurs® Le Corbusier® tinted. If the existing paint has a gloss or satin finish, lightly sand to roughen the surface and remove all dust to obtain a perfectly clean substrate.

Plasterboard, sealant, plaster and plaster derivatives, non-tannic wood and wood derivatives (porous substrates): sand to smooth the surface if necessary. Apply Undercoat Les Couleurs® Le Corbusier® tinted.

Powdery, chalking or questionable substrates and tannic wood: apply Solvent-Based Primer, followed by Undercoat Les Couleurs® Le Corbusier® tinted.

Application tools: apply with a 12 mm anti-drip roller for a rounded, lightly textured appearance, or a 10 mm roller for a smoother finish. Also suitable for airless or traditional spray gun application.

APPLICATION

Once Undercoat Les Couleurs® Le Corbusier® tinted is completely dry, apply two coats of Extra Matte Les Couleurs® Le Corbusier® (see General Information).

Tip: we recommend testing the dilution ratio on a small surface to determine the appropriate percentage (the paint should not pull; it should glide easily over the surface to be painted).

When using an airless or traditional spray gun, and depending on the equipment used, dilute the paint with 10% to 20% water. Test several times on a piece of cardboard or an inconspicuous area until the optimum dilution is achieved. The optimum dilution allows a neat application (good flow and levelling) and improved application comfort.

GENERAL INFORMATION

Appearance: deep matte.

Gloss: 2 GU (60°/85°).

Cleaning: wipeable – Class 2 wet scrub resistance⁽¹⁾.

Coverage: 14 m²/L per coat, depending on the application tools and selected dilution.

Drying time: 30 mn (dry to the touch).

Recoat time: approx. 4 h depending on temperature and air humidity.

Solid content: 63% (+/- 2%) in weight, 47% (+/- 2%) in volume.

Density: 1.55 g/cm³ (+/- 0.05) in white.

How to clean your equipment: water.

Packaging: 1L, 2.5L and 5L.

Storage: 1 year in its original unopened packaging. Keep away from frost.

Tinting: available in all 63 colors of the Les Couleurs® Le Corbusier® collection (5 bases).

Number of coats: 2 finishing coats.

Please note: some colors require 3 finishing coats:

(32051, 32090, 32100, 32101, 4320A, 4320D, 4320F, 4320K, 4320S, 4320T, 4320W).

HANDLE WITH CARE

Use in temperatures between +8°C and +35°C. Do not use when relative humidity reaches more than 70%.

For all colors in the Les Couleurs® Le Corbusier® collection, prior application of Undercoat Les Couleurs® Le Corbusier® tinted is essential to reveal the full depth and accuracy of the color.

REGULATORY INFORMATION

AFNOR Classification: Family I - Class 7a2/4a.

VOC⁽¹⁾ : the 2010 EU limit value for this product (cat A/a) is 30 g/L.

This product contains maximum 30 g/L VOC ready for use.

Safety: refer to the Safety Data Sheet (SDS). Complies with current legislation.

⁽¹⁾ Volatile Organic Compounds: Directive 2004/42/EC.

⁽²⁾ According to ISO 11998 and EN 13300, the paint film withstands cleaning with a soft sponge and a non-aggressive household cleaning product. However, there is a risk of burnishing, particularly with dark colors.

* Information on the emission of volatile substances into indoor air, presenting a risk of toxicity by inhalation, on the class scale from A+ (very low emissions) to C (high emissions).



Ressource is a certified Les Couleurs® Le Corbusier® licence holder. Les Couleurs Suisse AG is the exclusive worldwide licensor of the Le Corbusier colours – granted by the Fondation Le Corbusier®. Les Couleurs® Le Corbusier® are registered trademarks of Les Couleurs Suisse AG and the Fondation Le Corbusier®.

TDS No. 991 Edition 13 October 2026. This Technical Data Sheet cancels and replaces the previous editions for the same product. As techniques evolve constantly, it is the sole responsibility of our customers to check with our services - before use - that this Technical Data Sheet is the most recent edition.
Document available on our website ressource-peintures.com